



Parts for Trucks, Trailers & Buses

3

BELTS & HOSES

*Proven, reliable and
always innovative.*

TRP® offers reliable aftermarket products that are designed and tested to exceed customers' expectations regardless of the vehicle make, model or age.



BELTS • HOSES



Tested. Reliable. Guaranteed.

Belts & Hoses

Choosing the right replacement part or service for your vehicle—whether you own one, or a fleet—is one of the most important decisions you can make for your business. And, with tested TRP® parts it's an easy decision.

Regardless of the make you drive, TRP® quality replacement parts are engineered to fit your truck, trailer or bus. Choose the parts that give you the best value for your business. Check them out at an approved TRP® retailer near you.

The cross reference information in this catalog is based upon data provided by several industry sources and our partners. While every attempt is made to ensure the information presented is accurate, we bear no liability due to incorrect or incomplete information.

Product Availability

Due to export restrictions and market demands, not all products are always available in every location. Check for availability in your area with your local TRP® Distributor.

No part of this marketing material may be reproduced in any manner without written permission from TRP® North America.

TABLE OF CONTENTS

BELTS & HOSES

BELTS

Belts (Serpentine)	3-8
V-Belts	3-14

HOSES

AeroQuip Hoses	3-16
Air Brake Hose - Assembly Harness	3-16
Air Brake Hose - Polar Low Temp - 65°F Truck Air Brake Hose (J1402A)	3-17
Air Brake Hose - Tubing	3-17
Air Brake Hose Kit - Nylon Hose Dispenser Kits	3-19
Air Intake - Charge Air Hose	3-20
Cab Hose - Undercab Harness Hose	3-20
Coiled Air Hose (Individual)	3-21
Coiled Air Hose (Sets)	3-22
Dash Hose Harness	3-22
Fuel Hose - Fuel Line & Emission Control Hose	3-23
Fuel Hose - Fuel Line Return Assembly	3-24
Fuel Hose - Fuel & Oil Hardline	3-24

TRP® North America

750 Houser Way N.
Renton, WA 98057

www.trpparts.com

Fuel Hose - Fuel & Oil Hose - 30R7 . . .	3-25	HVAC Hose - Sleeper Coolant	3-48
Hand Valve Harness Hose	3-25	HVAC Hose - Suction Hose.	3-48
Heater Hose	3-26	HVAC Hose - Suction Hose (AeroQuip).	3-49
Heater Hose - Extreme Temperature Silicone Value Wall	3-27	HVAC Hose - Suction Hose (B Cab)	3-49
Heater Hose - General Purpose Heater Hose (Standard Duty)	3-28	HVAC Hose - Suction Hose (B Cab, ISX-EGR)	3-50
Heater Hose - High Performance Magnum Aramid (Severe Service) . . .	3-28	HVAC Hose - Under Sleeper HVAC Hardline	3-50
Harness Hose Assembly	3-29	Hydraulic Hoses - #04 Female SAE Rubber Covered Hose Assembly	3-50
Hose Jumpers - 3/8" Jumpers with ABS Fittings.	3-29	Hydraulic Hoses - #06 Female SAE 45° Flare Hose Assembly	3-51
Hose Jumpers - 1/2" Jumpers with ABS Fittings.	3-29	Hydraulic Hoses - #08 Female JIC Hose Assembly	3-51
Hose Jumpers - Peterbilt Jumper Kit	3-30	Hydraulic Hoses - #08 Female JIC x Female JIC 90° Hose Assembly	3-52
HVAC Hose	3-31	Hydraulic Hoses - #08 Female SAE Flare Air Hose Assembly	3-52
Size 6 Male 90° x Female 90°	3-39	Hydraulic Hoses - #16 Female JIC Hose Assembly	3-53
HVAC Hose - A/C Discharge Hose - Size 8	3-42	Miscellaneous Hoses	3-53
HVAC Hose - A/C Hose Hardline Assemblies	3-44	Molded Hoses	3-53
HVAC Hose - A/C Liquid Hose Assembly.	3-45	Power Steering Hose Assembly	3-55
HVAC Hose - A/C Sleeper Hose Assembly - Size 6	3-46	Power Steering Hose - "XT" Power Steering Push-On Hose	3-55
HVAC Hose - Condenser to Filter Hose Assembly - Size 6	3-46	Push-On Hose - Fabric Cover	3-56
HVAC Hose - Coolant	3-46	Push-On Hose - Rubber Cover	3-56
HVAC Hose - Freon Compressor Hose Assemblies	3-47	Radiator Hose - 2-1/2" EPDM ISX. . . .	3-57
HVAC Hose - Liquid to Cab, HVAC R/D Outlet x HVAC Cab TXV x A/C Hose	3-47	Radiator Hose - 90°	3-58
HVAC Hose - Sleeper Coolant	3-48	Radiator Hose - Extreme Temperature Reduced Reinforcement Silicone	3-58

Radiator Hose - Heavy Duty General Purpose	3-59	Transmission Hose Harness	3-72
Radiator Hose - High Performance Magnum Aramid (Severe Service) . . .	3-60	Transmission Oil Cooler - Straight Fittings	3-72
Radiator Hose - J20R1 D/C 2-Ply 3" . .	3-61	Truck Hose - Low Temperature (Arctic Hose)	3-73
Radiator Hose - J20R4	3-63	Truck Hose - Magnum Flex	3-73
Radiator Hose - Lower	3-63	Trailer Hose Assembly	3-74
Radiator Hose - Lower Radiator Coolant Hose	3-63	Turbo Hose - Silicone Turbocharger Double Hump Hoses	3-75
Radiator Hose - Lower Radiator Coolant Hose - C12	3-64	Windshield Washer & Vacuum Tubing	3-75
Radiator Hose - Overflow	3-64	Wire Braid Hose Assemblies	3-76
Radiator Hose - Upper	3-65	Wire Braid Hose Assembly - Air or Water Hose Assembly	3-81
Steel Radiator Vent Tubing	3-65		
Steel Radiator Vent Tubing - 3/8"	3-66		
Swivel Hoses - Female Swivel to Female Swivel Hose Assemblies	3-66		
Swivel Hoses - Female Swivel to Male Pipe Hose Assemblies	3-66		
Teflon Hoses	3-67		
Teflon Hoses - Compressor Discharge Hose - #10 Female SAE	3-68		
Teflon Hoses - Compressor Discharge Hose - 7/8- 14 UNF (Both Ends)	3-69		
Teflon Hoses - Compressor Discharge Hose - Size 10	3-69		
Teflon Hoses - Compressor Discharge Hose - Size 10 Fitting Male x Female	3-69		
Teflon Hoses - Compressor Discharge Hose - Size 10 Fitting Male x Male	3-70		
Teflon Hoses - Compressor Discharge Hose - Size 12	3-71		
Teflon Hoses - High Temp MP	3-72		



HOSES

FEATURES & BENEFITS

- » Fluorocarbon-lined charge air bellows with clamp saddle and flared ends
- » Hose assemblies are crimped and ready for installation
- » Three and four-ply silicone-wrapped coolant hoses are reinforced with fabric to resist hardening, cracking and leaking

RELATED PARTS

- » Hose Clamps
- » Coolant



RADIATOR HOSES

TRP Hoses are engineered for the life of your truck. Turbocharger bellows are used on diesel truck engines to deliver pressurized air intake to the charge air intercooler and intake manifold. Custom designed coolant and heater hoses are engineered to OE specifications and use a variety of reinforcements for heavy-duty pressure connections in hostile engine environments. Ideal for extreme temperatures and various pressure ranges, TRP hoses continuously provide high performance levels.



Scan the code for more information.
Get the free mobile app at <http://gettag.mobi>



BELTS

FEATURES & BENEFITS

- » Polyester cording provides maximum power transfer and tension holding capability for the life of the belt
- » Three-ply construction helps prevent belt roll-over, reduces noise and protects against chemical-related deterioration

RELATED PARTS

- » Tensioners
- » Idler Pulleys



NOTES

Edge cord failure can be caused by worn drive system pulleys, brackets or bearings. These components should always be inspected and replaced as necessary.



V-BELTS

TRP V-Belts are constructed with three plies of fabric as well as a specially formulated treatment of the polyester cord that provides strength, stability and reliability. Full sidewall contact combined with a cogged design prevents slippage around pulleys and ensures superior performance.

POPULAR PARTS

TRP®	Description
17591BLT	V-Belt 17/32 TW x 59 EL SGL
17611BLT	V-Belt 17/32 TW x 61 EL SGL
17621BLT	V-Belt 17/32 TW x 62 EL SGL
22550BLT	V-Belt 22/32 TW x 55 EL SGL
22570BLT	V-Belt 22/32 TW x 57 EL SGL
28413BLT	V-Belt 28/32 TW x 41 EL SGL
28437BLT	V-Belt 28/32 TW x 43-1/2 EL S



Scan the code for more information.
Get the free mobile app at <http://gettag.mobi>



BELTS

FEATURES & BENEFITS

- » Manufactured to SAE specifications by using specially blended rubber
- » Provides exact length specifications for maximum life of the belt
- » Rubber compound blends for specific applications provide excellent heat, wet-slip, noise and oil resistance

RELATED PARTS

- » Tensioners
- » Idler Pulleys



High Strength


POLY RIB BELTS

TRP Poly Rib Belts are used to transmit power in a multitude of applications. This “diesel grade” belt features more cords per inch than similar sized conventional light-duty belts in order to meet higher torque and power pulses found in today’s demanding diesel engines. TRP Poly Rib Belts are constructed with a reinforced rubber compound to ensure long life.



Scan the code for more information.
Get the free mobile app at <http://gettag.mobi>

BELTS


Hoses

See Page 3-16

BELTS (SERPENTINE)

Table 3-1: Poly Belts

Part No.	Size
4 Rib - HV1 (EPDM)/ POLY CORD	
4040327BLT	840mm
4040332BLT	845mm
4040470BLT	1195mm
5 Rib - HV1 (EPDM)/ POLY CORD	
4050320BLT	815mm
4050370BLT	940mm
4050440BLT	1120mm
4050845BLT	1245mm
4050545BLT	1390mm
4050845BLT	2145mm
6 Rib	
4060537BLT	1365mm
4060560BLT	1422mm
4060635BLT	1613mm
6 Rib - ENDURANCE/ POLY	
D84-1000-6061000	1000mm
D84-1000-6061205	1205mm
D84-1000-6061250	1250mm
D84-1000-6061290	1290mm
D84-1000-6061325	1325mm
D84-1000-6061470	1470mm
D84-1000-6061535	1535mm
D84-1000-6061565	1565mm
D84-1000-6061620	1620mm
D84-1000-6061690	1690mm
D84-1000-6061695	1695mm
D84-1000-6061700	1700mm
D84-1000-6061720	1720mm
D84-1000-6061750	1750mm
D84-1000-6061740	1740mm



Part No.	Size
D84-1000-6060950	950mm
D84-1000-6060970	970mm
D84-1000-6061750	1750mm
D84-1000-6061870	1870mm
D84-1000-6062175	2175mm
D84-1000-6122450	2450mm
6 Rib - Orion Heavy Duty (EPDM)/ POLY	
D84-1000-3060970	970mm
D84-1000-3061050	1050mm
D84-1000-3061085	1085mm
D84-1000-3061105	1105mm
D84-1000-3061190	1190mm
D84-1000-3061215	1215mm
4060502RPBLT	1275mm
D84-1000-3061280	1280mm
D84-1000-3061310	1310mm
D84-1000-3061315	1315mm
D84-1000-3061340	1340mm
D84-1000-3061370	1370mm
4060551RPBLT	1400mm
D84-1000-3061420	1420mm
4060561RPBLT	1425mm
D84-1000-3061440	1440mm
D84-1000-3061450	1450mm
D84-1000-3061460	1460mm
4060579RPBLT	1470mm
4060594RPBLT	1510mm
D84-1000-3061560	1560mm
D84-1000-3061620	1620mm
D84-1000-3061700	1700mm
D84-1000-3061850	1850mm
6 Rib - HV1 (EPDM)/ POLY CORD	
4060360BLT	915mm
4060380BLT	965mm
4060465BLT	1180mm
4060487RKBLT	1230mm
4060487RPBLT	1230mm

Part No.	Size
4060497RPBLT	1270mm
4060500RPBLT	1270mm
4060522RPBLT	1330mm
4060524RPBLT	1335mm
4060531RPBLT	1345mm
4060545RPBLT	1390mm
4060578BLT	1465mm
4060583RPBLT	1485mm
4060589RPBLT	1500mm
4060615BLT	1500mm
4060606RPBLT	1537mm
4060620BLT	1575mm
4060628RPBLT	1600mm
4060642BLT	1630mm
4060672BLT	1715mm
4060680BLT	1730mm
4060710BLT	1805mm
4060715BLT	1815mm
4060736EPBLT	1865mm
4060747BLT	1905mm
4060760BLT	1930mm
4060790BLT	2005mm
4060827BLT	2110mm
4060860BLT	2185mm
4060865BLT	2195mm
4060887BLT	2225mm
4060895BLT	2275mm
4060930BLT	2360mm
4060935BLT	2375mm
4060940BLT	2390mm
4060945BLT	2400mm
4060960BLT	2440mm
4060987BLT	2515mm
4061000BLT	2540mm
4061010BLT	2565mm
4061203BLT	3050mm

Part No.	Size
7 Rib - GOLD LABEL HV1 (EPDM)/ POLY CORD	
4070425BLT	1080mm
4070640BLT	1625mm
4070685BLT	1740mm
4070705BLT	1790mm
4070975BLT	2475mm
4071005BLT	2555mm
4071037BLT	2645mm
4071145BLT	2895mm
8 Rib	
4080485BLT	1232mm
4080495BLT	1257mm
4080560BLT	1422mm
4080565BLT	1435mm
4080570BLT	1448mm
4080575BLT	1461mm
4080580BLT	1473mm
4080585BLT	1486mm
4080700BLT	1778mm
4080715BLT	1816mm
4080725BLT	1842mm
4080735BLT	1867mm
4080740BLT	1880mm
4080755BLT	1918mm
4080760BLT	1930mm
4080767BLT	1949mm
4080790BLT	2007mm
4080825BLT	2096mm
4080855BLT	2172mm
4080897BLT	2280mm
4080952BLT	2419mm
8 Rib - ENDURANCE/ POLY	
D84-1000-6081735	1735mm

Part No.	Size
D84-1000-6081750	1750mm
D84-1000-6081780	1780mm
D84-1000-6081820	1820mm
D84-1000-6081850	1850mm
D84-1000-6081855	1855mm
D84-1000-6081880	1880mm
D84-1000-6081910	1910mm
D84-1000-6081930	1930mm
D84-1000-6081935	1935mm
D84-1000-6081940	1940mm
D84-1000-6081950	1950mm
D84-1000-6082055	2055mm
D84-1000-6082060	2060mm
4080827APBLT	2120mm
D84-1000-6082130	2130mm
D84-1000-6082135	2135mm
D84-1000-6082155	2155mm
D84-1000-6082172	2172mm
D84-1000-6082175	2175mm
D84-1000-6082205	2205mm
D84-1000-6082260	2260mm
D84-1000-6082290	2290mm
D84-1000-6082295	2295mm
D84-1000-6082335	2335mm
D84-1000-6082355	2355mm
D84-1000-6082395	2395mm
D84-1000-6082420	2420mm
D84-1000-6082430	2430mm
D84-1000-6082448	2448mm
D84-1000-6082460	2460mm
D84-1000-6082520	2520mm
D84-1000-6082540	2540mm
D84-1000-6082560	2560mm
D84-1000-6082590	2590mm
D84-1000-6082600	2600mm
D84-1000-6082680	2680mm

Part No.	Size
8 RIB - ENDURANCE/ RUBBER	
D84-1000-8081735	1735mm
D84-1000-8081750	1750mm
D84-1000-8081855	1855mm
D84-1000-8081930	1930mm
D84-1000-8081940	1940mm
D84-1000-8082055	2055mm
8 RIB - ENDURANCE WITH WIRE BACKING	
D84-1000-6081803	1803mm
D84-1000-6082097	2097 mm
D84-1000-6082140	2140mm
D84-1000-6082165	2165mm
8 RIB - GOLD LABEL HV1 (EPDM)/ POLY CORD	
4080455BLT	1155mm
4080535BLT	1365mm
4080595BLT	1511mm
4080640BLT	1625mm
4080685BLT	1740mm
4080695BLT	1765mm
4080736APBLT	1865mm
4080752RPBLT	1905mm
4080793APBLT	2020mm
4080797APBLT	2032mm
4080803APBLT	2045mm
4080811RPBLT	2055mm
4080815APBLT	2065mm
4080819APBLT	2085mm
4080835APBLT	2110mm
4080835RPBLT	2120mm
4080839BLT	2135mm
20-8075BLT	2225mm
4080874APBLT	2225mm
4080876APBLT	2225mm
20-7422BLT	2255mm
4080894RPBLT	2275mm

Part No.	Size
20-8122BLT	2285mm
4080900APBLT	2285mm
4080903BLT	2300mm
4080913RPBLT	2325mm
4080915APBLT	2325mm
4080949RPBLT	2413mm
4080970APBLT	2465mm
4080976APBLT	2490mm
4080982APBLT	2490mm
4080988RPBLT	2515mm
4080994RPBLT	2520mm
4080995RPBLT	2520mm
4081006RPBLT	2555mm
4081018RPBLT	2590mm
40801024EPBLT	2605mm
4081033RPBLT	2630mm
4081124BLT	2860mm
4081223BLT	3106mm
8 RIB - ORION HEAVY DUTY (EPDM)/POLY	
D84-1000-3081803	1803mm
D84-1000-3081880	1880mm
D84-1000-3081970	1970mm
4080797BLT	2025mm
4080823BLT	2090mm
D84-1000-3082125	2125mm
4080850APBLT	2160mm
D84-1000-6082190	2190mm
4080878APBLT	2230mm
D84-1000-3082230	2230mm
4080904RPBLT	2295mm
4080913APBLT	2320mm
4080917RPBLT	2330mm
4080925RPBLT	2350mm
D84-1000-3082370	2370mm
D84-1000-3082380	2380mm
D84-1000-3082415	2415mm
D84-1000-3082420	2420mm

Part No.	Size
4080957APBLT	2430mm
4080961APBLT	2440mm
4080961RPBLT	2440mm
4080965APBLT	2450mm
4080965RPBLT	2450mm
4080972APBLT	2470mm
4080978RPBLT	2485mm
D84-1000-3082520	2520mm
D84-1000-3082540	2540mm
4081041BLT	2550mm
D84-1000-3082560	2560mm
D84-1000-3082590	2590mm
D84-1000-3082600	2600mm
4081031RPBLT	2620mm
D84-1000-3082630	2630mm
4081047RPBLT	2660mm
D84-1000-3082680	2680mm
4081089RPBLT	2765mm
D84-1000-3082790	2790mm
4081114RPBLT	2830mm
D84-1000-3082875	2875mm
D84-1000-3082880	2880mm
D84-1000-3082960	2960mm
8 Rib - NEOPRENE POLYESTER	
D84-1000-5082385	2385mm
8 Rib - ORION HEAVY DUTY (EPDM)/ RUBBER	
D84-1000-7082365	2365mm
9 Rib - HV1 (EPDM)/POLY CORD	
4090609BLT	1550mm

Part No.	Size
10 Rib	
4100660BLT	1676mm
10 Rib - ENDURANCE/ POLY	
D84-1000-6101765	1765mm
D84-1000-6101830	1830mm
D84-1000-6101860	1860mm
D84-1000-6101918	1918mm
D84-1000-6101965	1965mm
10PK2000	2000mm
D84-1000-6102045	2045mm
D84-1000-6102150	2150mm
D84-1000-6102215	2215mm
D84-1000-6102220	2220mm
D84-1000-6102235	2235mm
D84-1000-6102260	2260mm
D84-1000-6102340	2340mm
D84-1000-6102375	2375mm
D84-1000-6102405	2405mm
D84-1000-6102415	2415mm
D84-1000-6102430	2430mm
D84-1000-6102565	2565mm
D84-1000-6102635	2635mm
D84-1000-6102655	2655mm
D84-1000-6102705	2705mm
D84-1000-6102780	2780mm
D84-1000-6102845	2845mm
10 Rib - HV1 (EPDM)/ POLY CORD	
4100437BLT	1110mm
4100580BLT	1475mm
4100605BLT	1545mm
4100630BLT	1600mm
4100665BLT	1690mm
10 Rib - ORION HEAVY DUTY (EPDM)/ POLY	
D84-1000-3102175	2175mm

Part No.	Size
12 RIB POLY BELT	
4120931RPBLT	2365mm
12 RIB - ENDURANCE/ POLY	
D84-1000-6122130	2130mm
D84-1000-6122180	2180mm
D84-1000-6122195	2195mm
D84-1000-6122215	2215mm
D84-1000-6122230	2230mm
D84-1000-6122260	2260mm
D84-1000-6122295	2295mm
D84-1000-6122310	2310mm
D84-1000-6122340	2340mm
D84-1000-6122350	2350mm
D84-1000-6122375	2375mm
D84-1000-6122390	2390mm
D84-1000-6122425	2425mm
D84-1000-6122440	2440mm
D84-1000-6122470	2470mm
D84-1000-6122480	2480mm
D84-1000-6122485	2485mm
D84-1000-6122490	2490mm
D84-1000-6122505	2505mm
D84-1000-6122555	2555mm
D84-1000-6122560	2560mm
D84-1000-6122665	2665mm
D84-1000-6122710	2710mm
D84-1000-6122735	2735mm
D84-1000-6122760	2760mm
D84-1000-6122810	2810mm
D84-1000-6122855	2855mm
D84-1000-6122870	2870mm
D84-1000-6122970	2970mm
D84-1000-6123065	3065mm

Part No.	Size
12 RIB - ENDURANCE/ RUBBER	
D84-1000-8122215	2215mm
12 RIB - GOLD LABEL HV1 (EPDM)/ POLY CORD	
4120902BLT	2290mm
12 RIB - ORION HEAVY DUTY (EPDM)/ POLY	
D84-1000-3122260	2260mm
D84-1000-3122295	2295mm
4120911RPBLT	2315mm
D84-1000-3122350	2350mm
D84-1000-3122380	2380mm
D84-1000-3122400	2400mm
D84-1000-3122460	2460mm
D84-1000-3122480	2480mm
D84-1000-3122485	2485mm
D84-1000-3122500	2500mm
D84-1000-3122540	2540mm
D84-1000-3122640	2640mm
D84-1000-3122860	2860mm
D84-1000-3122990	2990mm
14 RIB	
4140585RKBLT	1485mm
14 RIB - ENDURANCE/ POLY	
14PK2310	2310mm
14 RIB - GOLD LABEL HV1 (EPDM)/ POLY CORD	
4140495BLT	1255mm
4140517BLT	1320mm
4140591RKBLT	1525mm
4140600BLT	1525mm
14 RIB - ORION HEAVY DUTY (EPDM)/ KEVLAR	
D84-1000-4141384	1384mm

V-BELTS

Table 3-2: V-Belts

Part No.	Outside Length	Depth	Outside CIRC
9/32" WIDE			
10344BLT	34-1/2"		
10461BLT	46-1/8"		
15/32" WIDE			
15325BLT	32-5/8"		
15340BLT	34"		
15391BLT	39-1/8"		
15396BLT	39-3/4"		
15425BLT	42-5/8"		
13435BLT	43-5/8"		
15440BLT	44"		
15445BLT	44-5/8"		
13454BLT	45-1/2"		
15461BLT	46-1/8"		
15475BLT	47-5/8"		
15491BLT	49-1/8"		
15521BLT	52-1/8"		
15542BLT	54-1/4"		
15585BLT	58-5/8"		
15605BLT	60-5/8"		
17/32" WIDE			
17245BLT	24-5/8"		
17281BLT	28-1/8"		
17291BLT	29-1/8"		
17295BLT	29-5/8"		
17386BLT	38-3/4"		
17425BLT	42-5/8"		
17456BLT	45-3/4"		
17470BLT	47"		
17521BLT	52-1/8"		
17521TTBLT	52-1/8"		
17525BLT	52-5/8"		

Part No.	Outside Length	Depth	Outside CIRC
17523BLT	52-3/8"		
17535BLT	53-5/8"		
17541BLT	54-1/8"		
17551BLT	55-1/8"		
17561BLT	56-1/8"		
17570BLT	57"		
17581BLT	58-1/8"		
17601BLT	60-1/8"		
17605BLT	60-5/8"		
17625BLT	62-5/8"		
17633BLT	63-3/8"		
17641BLT	64-1/8"		
17651BLT	65-1/8"		
21/32" WIDE			
BX59BLT			62"
BX83BLT			86"
22/32" WIDE			
22300BLT	30"		
22350BLT	35"		
22364BLT	36-1/2"		
22404BLT	40-1/2"		
22424BLT	42-1/2"		
22470BLT	47"		
22604-2KEVLAR-BLT	60-1/2"		
22490BLT	49"		
22544BLT	54-1/2"		
22574BLT	57-1/2"		
22590BLT	59"		
22610BLT	61"		
22624BLT	62-1/2"		
22634BLT	63-1/2"		
22650BLT	65"		
24/32" WIDE			
24443BLT	44-3/8"		

Part No.	Outside Length	Depth	Outside CIRC	Part No.	Outside Length	Depth	Outside CIRC
24313BLT	31-3/8"			A45BLT		11/32"	47"
24453BLT	45"			21/32" WIDE PREMIUM - BOTTOM COGGED INDUSTRIAL			
24467BLT	46-1/2"			BX33BLT		7/16"	36"
24483BLT	48"			BX77BLT		7/16"	80"
24493BLT	49"			BX81BLT		7/16"	84"
24653BLT	65-1/2"			16/32" WIDE PREMIUM - DOUBLE WRAPPED INDUSTRIAL			
28/32" WIDE				A42BLT		5/16"	44"
28457BLT	45-1/2"			AP46BLT		5/16"	48"
28487BLT	48-1/2"						
28493BLT	49"						
28513BLT	51"						
1-1/8" WIDE							
2/17311TTBLT			31-3/4"				
2/17511TTBLT			51-1/4"				
1-1/8" WIDE BANDED							
2/17451TTBLT			45-3/4"				
2/17491TTBLT			49-3/4"				
2/17544TTBLT			55-1/4"				
2/17641TTBLT			64-3/4"				
2/17651TTBLT			65-3/4"				
2/17671TTBLT			67-3/4"				
2/17701TTBLT			70-3/4"				
2/17731TTBLT			73-3/4"				
12/32" WIDE GOLD LABEL - VX WEDGE BOTTOM COGGED							
3VX750BLT		5/16"	75"				
3VX800BLT		5/16"	80"				
20/32" WIDE GOLD LABEL - VX WEDGE BOTTOM COGGED							
5VX900BLT		17/32"	90"				
16/32" WIDE PREMIUM - BOTTOM COGGED INDUSTRIAL							
A44BLT		11/32"	46"				

HOSES

Note: Standard dash sizes for hoses refers to inside diameter size. Standard dash sizes for tubing refer to the outside diameter size.

AEROQUIP HOSES

Table 3-3: Hose - AeroQuip Hoses

TRP® Part No.	Description
HE2087	FC332 AeroQuip Hose - Size 4 Textile
HE2091	FC332 AeroQuip Hose - Size 6 Textile
HE2095	FC332 AeroQuip Hose - Size 8 Textile
HE2104	FC332 AeroQuip Hose - Size 12 Textile

AIR BRAKE HOSE



Table 3-4: Hose - Air Brake Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
HE2224	3/8"	225	900	0.38	0.78	1.50	100'

AIR BRAKE HOSE - ASSEMBLY HARNESS

Table 3-5: Air Brake - Hose Assembly Harness

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
AIR BRAKE TUBING - 1/8" - 4 LINE							
HE4077	1/8"	n/a	n/a	n/a	n/a	n/a	n/a
AIR BRAKE DASH HARNESS - TUBES INCLUDED							
HE4337	-6	n/a	n/a	0.38	1.50	n/a	n/a

AIR BRAKE HOSE - POLAR LOW TEMP -65°F TRUCK AIR BRAKE HOSE (J1402A)



NOTE: Fittings shown without hose.



Belts

See Page 3-8

Table 3-6: Hose - Air Brake Hose - Polar Low Temp -65°F Truck Air Brake Hose (J1402A)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Standard Packaging Qty.
HE1006	-6	900	950	7-1/2"	n/a	n/a	30"	n/a
HE1828	-10	225	950	5"	8-3/4"	4"	36"	n/a
HE2131	-6	225	900	3/8"	3/4"	1-1/2"	n/a	25'
HE2143	-8	225	900	1/2"	7/8"	1-3/4"	n/a	25'

AIR BRAKE HOSE - TUBING

Table 3-7: Hose - Air Brake Hose - Tubing

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Color	Standard Packaging Qty.
AIR BRAKE TUBING - TYPE A								
HE1448	-4	225	900	1/4"	5/8"	1-1/2"	n/a	50'
HE14502	-4	225	900	1/4"	5/8"	1-1/2"	n/a	500' Spool
HE2168	-6	225	900	3/8"	3/4"	1-3/4"	n/a	250' Spool
HE21701	-6	225	900	3/8"	3/4"	1-3/4"	n/a	600' Spool
HE21712	-6	225	900	3/8"	3/4"	1-3/4"	n/a	50'
HE21831	-8	225	900	1/2"	7/8"	2"	n/a	250' Spool
HE2184	-8	225	900	1/2"	7/8"	2"	n/a	50'
AIR BRAKE TUBING - TYPE A - NYLON (J844A)								
HE2189	-3	400	1,200	n/a	3/16"	3/5"	Black	100'

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Color	Standard Packaging Qty.
HE2194	-2	400	1,200	n/a	1/8"	3/8"	Black	2000'
HE2195	-2	400	1,200	n/a	1/8"	3/8"	Blue	100'
HE21971	-2	400	1,200	n/a	1/8"	3/8"	Black	100'
HE2202	-4	400	1,200	n/a	1/4"	1"	Yellow	100'
HE2203	-4	400	1,200	n/a	1/4"	1"	Blue	100'
HE22042	-4	400	1,200	n/a	1/4"	1"	Green	100'
HE22051	-4	400	1,200	n/a	1/4"	1"	Black	100'
HE22061	-4	400	1,200	n/a	1/4"	1"	Purple	1000'
HE2207	-4	400	1,200	n/a	1/4"	1"	Black	1000'
HE2208	-4	400	1,200	n/a	1/4"	1"	Blue	1000'
HE22091	-4	400	1,200	n/a	1/4"	1"	Red	1000'
HE22102	-4	400	1,200	n/a	1/4"	1"	Green	1000'
HE2211	-4	400	1,200	n/a	1/4"	1"	Yellow	1000'
HE22121	-4	400	1,200	n/a	1/4"	1"	Silver	1000'
HE22131	-4	400	1,200	n/a	1/4"	1"	Brown	1000'
HE2214	-4	400	1,200	n/a	1/4"	1"	Orange	1000'
HE2217	-5	400	1,200	n/a	5/16"	1-1/4"	Black	100'
HE2218	-4	400	1,200	n/a	1/4"	1"	Orange	100'

AIR BRAKE TUBING - TYPE B NYLON (J844B)

HE2221	-6	400	1,200	n/a	3/8"	1-1/2"	Black	100'
HE22231	-6	400	1,200	n/a	3/8"	1-1/2"	Blue	500'
HE22251	-6	400	1,200	n/a	3/8"	1-1/2"	Green	500'
HE2227	-6	400	1,200	n/a	3/8"	1-1/2"	Red	500'
HE2230	-6	400	1,200	n/a	3/8"	1-1/2"	Yellow	100'
HE2231	-6	400	1,400	n/a	3/8"	1-1/2"	Orange	100'
HE22321	-6	400	1,200	n/a	3/8"	1-1/2"	Green	100'
HE2233	-8	400	1,200	n/a	1/2"	2"	Black	500'
HE2234	-8	400	1,200	n/a	1/2"	2"	Black	100'
HE22351	-8	400	1,200	n/a	1/2"	2"	Orange	100'
HE2236	-8	400	1,200	n/a	1/2"	2"	Green	100'
HE2237	-6	400	1,200	n/a	3/8"	1-1/2"	Blue	100'
HE2238	-6	400	1,200	n/a	3/8"	1-1/2"	Red	100'
HE2239	-8	400	1,200	n/a	1/2"	2"	Red	100'
HE2242	-8	400	1,200	n/a	1/2"	2"	Blue	100'
HE2249	1/2"	400	900	0.5	0.88	1.75	Purple	500'

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Color	Standard Packaging Qty.
HE2253	-8	400	1,200	n/a	1/2"	2"	Blue	500'
HE2255	-8	400	1,200	n/a	1/2"	2"	Green	500'
HE2257	-8	400	1,200	n/a	1/2"	2"	Yellow	500'
HE2259	-10	400	1,200	n/a	5/8"	2-1/2"	Black	250'
HE2260	-10	400	1,200	n/a	5/8"	2-1/2"	Black	100'
HE22611	-10	400	1,200	n/a	5/8"	2-1/2"	Green	250'
HE2262	5/8"	400	1,200	n/a	5/8"	2-1/2"	Red	250'
HE22631	-10	400	1,200	n/a	5/8"	2-1/2"	Yellow	250'
HE2265	5/8"	400	1,200	n/a	0.63	2.5	Green	100'
HE2266	-10	400	1,200	n/a	5/8"	2-1/2"	Orange	250'
HE2270	5/8"	400	1,200	n/a	0.63	2.5	Blue	250'
HE2272	-12	400	1,200	n/a	3/4"	3"	Black	250'
HE22731	-12	400	1,200	n/a	3/4"	3"	Black	100'
HE2279	-12	400	1,200	n/a	3/4"	3"	Orange	250'
HE4079	5/32"	400	1,200	n/a	3/16"	1/2"	Black	100'

AIR BRAKE HOSE KIT - NYLON HOSE DISPENSER KITS

Table 3-8: Hose - Air Brake Hose Kit - Nylon Hose Dispenser Kits

TRP® Part No.	Size	Length	Qty.	Color
NYLON HOSE DISPENSER KIT, ALL BLACK HOSE KIT				
HE1982	1/8"	n/a	200' reel	Black
HE1985	5/32"	n/a	200' reel	Black
HE1988	1/4"	n/a	200' reel	Black
HE1991	5/16"	n/a	200' reel	Black
HE1994	3/8"	n/a	200' reel	Black
HE1997	1/2"	n/a	200' reel	Black
HE2000	5/8"	n/a	75' reel	Black
NYLON HOSE DISPENSER KIT, COLORED HOSE KIT				
HE1990	1/4"	n/a	200' reel	Purple
HE1996	3/8"	n/a	200' reel	Green
HE1999	1/2"	n/a	200' reel	Yellow
HE2003	5/8"	n/a	75' reel	Orange

AIR INTAKE - CHARGE AIR HOSE

Table 3-9: Air Intake - Charge Air Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)
HE4479	4"	n/a	25	4.00	4.23	n/a
HE9511	4"	.27 mpa	n/a	4.30	n/a	n/a
HE9601	4"	n/a	n/a	n/a	n/a	n/a

CAB HOSE - UNDERCAB HARNESS HOSE



Table 3-10: Hose - Undercab Harness Hose

TRP® Part No.	Description
HE2351	Undercab Harness Hose
HE2303	Undercab Harness Hose

COILED AIR HOSE (INDIVIDUAL)



Table 3-11: Hose - Coiled Air Hose (Individual)

TRP® Part No.	Length	Leads	Color
HE23782	15'	12"/12"	Blue
HE23791	15'	12"/12"	Red
HE23801	15'	40"/6"	Blue
HE23811	15'	40"/6"	Red
HE23901	10'	12"/18"	Red
HE23911	10'	12"/18"	Blue
HE2394	15'	48"/12"	Blue
HE23951	15'	48"/12"	Red
HE2401	12'	37"/12"	Blue
HE2402	12'	37"/12"	Red
HE2857	12'	6"/6"	Red
HE2858	12'	6"/6"	Blue

COILED AIR HOSE (SETS)



Table 3-12: Hose - Coiled Air Hose (Sets)

TRP® Part No.	Length	Leads	Color
HE10121	12'	12"/12"	Red & Blue
HE10151	15'	12"/12"	Red & Blue
HE10201	20'	12"/12"	Red & Blue
HE2393	15'	12"/12"	Red & Blue
HE2397	12'	6"/6"	Red & Blue
HE2399	10'	12"/18"	Red & Blue
HE2425	12'	48"/12"	Red & Blue
HE2427	15'	48"/12"	Red & Blue
HE2429	12'	12"/12"	Red & Blue
HE2436	15'	24"/12"	Red & Blue
HE24391	25'	12"/12"	Red & Blue
HE24541	15'	40"/6"	Red & Blue
HE4115	15'	12"/40"	Red & Blue

DASH HOSE HARNESS

Table 3-13: Hose - Dash Hose Harness

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)
HE4337	-6	n/a	n/a	0.38	1.50	n/a

FIFTH WHEEL THERMOPLASTIC SLIDER COIL



Table 3-14: Hose - Fifth Wheel Thermoplastic Slider Coil

TRP® Part No.	Size (A)	Tubing Outside Diameter	Size (B)	Thread	Length	Application
HE24111	-4	1/4"	n/a	n/a	6'	Coiled line only
HE24151	-4	1/4"	n/a	n/a	6'	Coiled line only
HE23331	-4	1/4"	n/a	n/a	6'	Coiled line with fittings

FUEL HOSE - FUEL LINE & EMISSION CONTROL HOSE

Table 3-15: Hose - Fuel Hose - Fuel Line & Emission Control Hose

TRP® Part No.	Size (A)	Max. PSI	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Standard Packaging Qty.
HE2502	-4	50	175	1/4"	25'
HE2528	-5	50	175	5/16"	25'
HE2541	-6	50	175	3/8"	25'

FUEL HOSE - FUEL LINE RETURN ASSEMBLY



Table 3-16: Hose - Fuel Hose - Fuel Line Return Assembly

TRP® Part No.	Inside Diameter (in.)	Length
HE23261	n/a	26"

FUEL HOSE - FUEL & OIL HARDLINE



Table 3-17: Hose - Fuel & Oil Hardline

TRP® Part No.	Size (A)	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE2320	-5	350	1,000	5/16"	9/16"	3.00	550'

FUEL HOSE - FUEL & OIL HOSE - 30R7



Table 3-18: Hose - Fuel & Oil Hose - 30R7

TRP® Part No.	Inside Diameter (in.)	Length
HE2314	1/4"	n/a

HAND VALVE HARNESS HOSE



Table 3-19: Hose - Hand Valve Harness Hose

TRP® Part No.	Description
HE2229	Hand Valve Harness Hose
HE2345	Hand Valve Harness Hose
HE2357	Hand Valve Harness Hose

HEATER HOSE



Table 3-20: Hose - Heater

TRP® Part No.	Size	Max. PSI (Working Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Length
HEATER HOSE - SIZE 3/8" - BLACK					
HE5202	-6	n/a	n/a	n/a	50'
HEATER HOSE - SIZE 6 - J20R3D					
HE5401	-6	n/a	n/a	n/a	50'
HEATER HOSE - SIZE 8 - J20R3D					
HE5205	-8	n/a	0.50	0.81	50'
HE5305	-8	n/a	0.5	0.81	50'
HE5405	-8	n/a	0.50	0.84	50'
HEATER HOSE - SIZE 10 - J20R3D					
HE5310	-10	n/a	0.63	0.94	50'
HEATER HOSE - SIZE 12 - J20R3D					
HE5315	-12	n/a	0.75	1.06	50'
HEATER HOSE - SIZE 16 - J20R3D					
HE5420	-16	175	1.00	1.33	50'

HEATER HOSE - EXTREME TEMPERATURE SILICONE VALUE WALL



Table 3-21: Hose - Extreme Temperature Silicone Value Wall Heater Hose

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)	Length	Standard Packaging Qty.
HE2919	-4	1/4"	11/16"	25'	
HE2924	-5	5/16"	3/4"	25'	
HE2932	-6	3/8"	13/16"	25'	
HE2934	-6	3/8"	13/16"	50'	
HE2939	-6	3/8"	13/16"	600'	
HE29451	-8	1/2"	15/16"	25'	
HE29471	-8	1/2"	15/16"	50'	n/a
HE2965	-10	5/8"	13/16"	400'	n/a
HE3625	-10	5/8"	13/16"	25'	Box
HE3628	-10	5/8"	13/16"	50'	Box
HE3755	-12	3/4"	1-1/16"	25'	Box
HE3758	-12	3/4"	1-1/16"	50'	Box
HE3833	-12	3/4"	1-1/16"	300'	Spool
HE3950	-16	1"	1-3/8"	25'	Box

HEATER HOSE - GENERAL PURPOSE HEATER HOSE (STANDARD DUTY)



Table 3-22: Hose - General Purpose Heater Hose (Standard Duty)

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)	Length	Standard Packaging Qty.
HE5210	-10	5/8"	15/16"	50'	n/a
HE5215	-12	3/4"	1-1/16"	50'	n/a
HE5220	-16	1"	1-5/16"	50'	n/a

HEATER HOSE - HIGH PERFORMANCE MAGNUM ARAMID (SEVERE SERVICE)



Table 3-23: Hose - High Performance Magnum Aramid Heater Hose (Severe Service)

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)	Length	Standard Packaging Qty.
HE21651	-10	5/8"	n/a	700'	n/a
HE2178	-12	3/4"	n/a	700'	n/a
HE5410	-10	5/8"	1"	50'	n/a
HE5415	-12	3/4"	1-3/16"	50'	n/a

HARNESS HOSE ASSEMBLY

Table 3-24: Harness - Hose Assembly

TRP® Part No.	Description
HE4114	Harness Hose Assembly

HOSE JUMPERS - 3/8" JUMPERS WITH ABS FITTINGS

Table 3-25: Hose Jumpers - 3/8" Jumpers with ABS Fittings

TRP® Part No.	Size	Length
HE0618	-6	18"
HE0621	-6	21"
HE0624	-6	24"
HE0627	-6	27"
HE0630	-6	30"
HE0633	-6	33"
HE0636	-6	36"
HE0639	-6	39"
HE0642	-6	42"

HOSE JUMPERS - 1/2" JUMPERS WITH ABS FITTINGS

Table 3-26: Hose Jumpers - 1/2" Jumpers with ABS Fittings

TRP® Part No.	Size	Length
HE0818	-8	18"
HE0821	-8	21"
HE0824	-8	24"
HE0827	-8	27"
HE0830	-8	30"
HE0833	-8	33"
HE0834	-8	34"
HE0836	-8	36"

TRP® Part No.	Size	Length
HE0839	-8	39"
HE0840	-8	40"
HE0842	-8	42"
HE0849	-8	49"
HE0862	-8	62"

HOSE JUMPERS - PETERBILT JUMPER KIT



NOTE: Fitting shown without hose.

Table 3-27: Hose Jumpers - Peterbilt Jumper Kit

TRP® Part No.	Size	Length
HE1310	-6	19"
HE1312	-6	21"
HE1318	-6	27"
HE1320	-6	39"
HE1322	-6	31"
HE1334	-6	43"
HE1348	-6	53"
HE1509	-8	13"
HE15151	-8	19"
HE1519	-8	23"
HE1522	-8	26"
HE1527	-8	31"
HE1529	-8	33"
HE1547	-8	51"

HVAC HOSE - ASSEMBLIES



HE4078

NOTE: Fitting shown without hose.

Table 3-28: HVAC Hose Assemblies

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE4078	-12	500	1750	0.63	0.92	4.00	n/a
HE23602	-10	500	1750	0.50	0.76	3.00	n/a
HE3396	-8	500	2500	0.41	0.68	2.50	n/a
HE0310	-6	500	2500	0.31	0.58	2.00	n/a
HE0436	-6	500	2500	0.31	0.58	2.00	n/a

CRIMPED ASSEMBY - 10° x 90°

Table 3-29: HVAC - Hose Assemblies - Crimped 10° x 90°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE5954	n/a	n/a	n/a	n/a	n/a	n/a	86"	n/a

CRIMPED, FEMALE SWIVEL 45° ELBOW O-RING x MALE SWIVEL STRAIGHT O-RING

NOTE: Fitting shown without hose.

Table 3-30: HVAC - Hose - Assemblies - Crimped, Female Swivel 45° Elbow O-Ring x Male Swivel Straight O-Ring

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2743	-6	500	2500	0.31	0.58	2.00	2000 mm	n/a
HE27781	-6	500	2500	0.31	0.58	2.00	2275 mm	n/a

CRIMPED P80 HOSE x 10 FEMALE 90° x 10 MALE 7/8" x 18

Table 3-31: HVAC - Hoses - Crimped P80 Hose x 10 Female 90° x 10 Male 7/8" x 18

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE4154	-12	500	2500	0.75	1.09	4.50	n/a	69"

FEMALE 90° x FEMALE 90°

NOTE: Fitting shown without hose.

Table 3-32: HVAC -Hose - Assemblies - Female 90° x Female 90°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE6652	-8	500	2500	0.41	0.68	2.50	n/a	82"

FEMALE SWIVEL 90° ELBOW O-RING x #6 HVAC LIQUID FITTING x #6 HVAC HOSE x STRAIGHT FEMALE

Table 3-33: HVAC - Hose Assemblies - Female Swivel 90° Elbow O-Ring x #6 HVAC Liquid Fitting x #6 HVAC Hose x Straight Female

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE3560	-6	500	2500	0.31	0.58	2.00	1075 mm	n/a

FEMALE SWIVEL 90° ELBOW O-RING x FEMALE 90° ELBOW WITH COMPRESSOR ADAPTER



NOTE: Fitting shown without hose.

Table 3-34: HVAC - Hose Assemblies - Female Swivel 90° Elbow O-Ring x Female 90° Elbow with Compressor Adapter

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2379	-12	500	1750	0.63	0.92	4.00	2800 mm	n/a

FEMALE STRAIGHT x FEMALE STRAIGHT

Table 3-35: HVAC - Hose Assemblies - Female Straight x Female Straight

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE40772	-12	500	1750	0.63	0.92	4.00	1100 mm	n/a

MALE SWIVEL STRAIGHT O-RING x FEMALE 90° ELBOW WITH COMPRESSOR ADAPTER



NOTE: Fitting shown without hose.

Table 3-36: HVAC - Hose Assemblies - Male Swivel Straight O-Ring x Female 90° Elbow with Compressor Adapter

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2395	-12	500	1750	0.63	0.92	4.00	1250 mm	n/a

MALE SWIVEL STRAIGHT O-RING X MALE 90° #12 w/ SERVICE PORT



NOTE: Fitting shown without hose.

Table 3-37: HVAC - Hose Assemblies - Male Swivel Straight O-Ring x Male 90° #12 w/ Service Port

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2380	-12	500	1750	0.63	0.92	4.00	1750 mm	n/a
HE2385	-12	500	1750	0.63	0.92	4.00	1925 mm	n/a

MALE STRAIGHT WITH SWITCH PORT X MALE 90° #12 WITH SERVICE PORT



NOTE: Fitting shown without hose.

Table 3-38: HVAC - Hose Assemblies - Male Straight with Switch Port x Male 90° #12 with Service Port

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2383	-12	500	1750	0.63	0.92	4.00	1750 mm	n/a

HVAC HOSE - A/C DISCHARGE HOSE

Table 3-39: Hose - HVAC - Hose Assembly - Size 8

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE22381	-8	500	2500	0.41	0.74	3.00	n/a	48"

R12 - SIZE 10 MALE 90° X SIZE 10 FEMALE 90°

Table 3-40: Hose - HVAC - Assemblies - R12 - Size 10 Male 90° x Size 10 Female 90°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE22301	-10	500	2500	0.50	0.86	3.50	52"	n/a

R134A - SIZE 10

Table 3-41: HVAC - Hose Assemblies - R134A - Size 10

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE0376	-10	500	1750	0.50	0.76	3.00	2600 mm	n/a

R134A - SIZE 6



NOTE: Fitting shown without hose.

Table 3-42: HVAC - Hose Assemblies - R134A - Size 6

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE3160	-6	500	2500	0.31	0.58	2.00	n/a	n/a

R134A - SIZE 8

Table 3-43: HVAC - Hose Assemblies - R134A - Size 8

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE22381	-8	500	2500	0.41	0.74	3.00	n/a	n/a

R134A - SIZE 10 PAD 90° X SIZE 12 MALE 90° (SWV)



NOTE: Fitting shown without hose.

Table 3-44: HVAC - Hose Assemblies - R134A - Size 10 Pad 90° x Size 12 Male 90° (SWV)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE6259	-12	500	1750	0.63	0.92	4.00	48"	n/a

R134A - SIZE 12 R134A FEMALE STRAIGHT X FEMALE



NOTE: Fitting shown without hose.

Table 3-45: HVAC - Hose Assemblies - R134A - Size 12 R134A Female Straight x Female

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE1930	-12	500	1750	0.63	0.92	4.00	n/a	n/a

Size 6

Table 3-46: HVAC - Hose Assemblies - Size 6

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2369	-6	500	2500	0.31	0.58	2.00	n/a	n/a
HE3232	-6	500	2500	0.31	0.58	2.00	600mm	n/a
HE3860	-6	500	2500	0.31	0.58	2.00	n/a	n/a
HE4063	-6	500	2500	0.31	0.58	n/a	n/a	n/a

SIZE 6 - P80 CRIMPED - 45° x 90°



NOTE: Fitting shown without hose.

Table 3-47: HVAC - Hose Assemblies - Size 6 - P80 Crimped - 45° x 90°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE4361	-6	500	2500	0.31	0.62	2.00	92"	n/a

SIZE 6 - P80 CRIMPED - 86° x 46°



NOTE: Fitting shown without hose.

Table 3-48: HVAC - Hose Assemblies - Size 6 - P80 Crimped - 86° x 46°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE13451	-6	500	2500	0.31	0.58	2.00	155-13/32"	n/a

SIZE 6 MALE 90° x FEMALE 90°

Table 3-49: HVAC - Hose Assemblies - Size 6 Male 90° x Female 90°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE9775	-6	2250	9000	0.31	0.68	4.00	n/a	n/a

SIZE 6 FEMALE 90° x MALE STRAIGHT



NOTE: Fitting shown without hose.

Table 3-50: HVAC - Hose Assemblies - Size 6 Female 90° x Male Straight

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2588	-12	500	1750	0.63	0.92	4.00	n/a	n/a

SIZE 8 MALE 90° x FEMALE STRAIGHT



NOTE: Fitting shown without hose.

Table 3-51: HVAC - Hose Assemblies - Size 8 Male 90° x Female Straight

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE9713	-8	500	2500	0.41	0.68	2.50	n/a	n/a

SIZE 12 x 10 FEMALE 7/8 " x 14 STRAIGHT, 10 PAD 90° MALE



HE2533

NOTE: Fitting shown without hose.

Table 3-52: HVAC - Hose Assemblies - Size 12 x 10 Female 7/8" x 14 Straight, 10 Pad 90° Male

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2533	-12	500	1750	0.63	0.92	4.00	43"	n/a
HE2544	-12	500	1750	0.63	0.92	4.00	52"	n/a
HE2552	-12	500	1750	0.63	0.92	4.00	60"	n/a

SIZE 12

Table 3-53: HVAC - Hose Assemblies - Size 12

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2372	-12	500	1750	0.63	0.92	4.00	n/a	n/a
HE3059	-12	500	1750	0.63	0.92	4.00	n/a	n/a

SIZE 12 FEMALE 90° MALE STRAIGHT

Table 3-54: HVAC - Hose Assemblies - Size 12 Female 90° Male Straight

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE5201	-10	n/a	n/a	n/a	n/a	n/a	n/a	n/a

SIZE 12 FEMALE STRAIGHT



NOTE: Fitting shown without hose.

Table 3-55: HVAC - Hose Assemblies - Size 12 Female Straight

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE2396	-12	500	1750	0.63	0.92	4.00	n/a	n/a

T300, ISC ENGINE, J2064



NOTE: Fitting shown without hose.

Table 3-56: HVAC - Hose Assemblies - T300, ISC Engine, J2064

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE3551	-12	500	1750	0.63	0.92	4.00	1200 mm	n/a

DISCHARGE HOSE (BULK)

Table 3-57: Hose - HVAC - A/C Discharge Hose - Size 8

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
A/C DISCHARGE HOSE - SIZE 8								
HE0747	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE0995	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE1176	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE1177	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE2997	-8	500	2500	0.41	0.68	2.50	92"	n/a
HE3000	-8	500	2500	0.41	0.68	2.50	97"	n/a
HE3735	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3741	-8	500	2500	0.41	0.68	2.50	11"	n/a
HE3742	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3926	-8	500	2500	0.41	0.68	2.50	49-1/4"	n/a
HE3927	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3958	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE4047	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE4049	-8	500	2500	0.41	0.68	2.50	n/a	n/a

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
HE9939	-8	500	2500	0.41	0.68	2.50	n/a	n/a

A/C DISCHARGE HOSE - SIZE 10

HE0500	-10	500	1750	0.50	0.76	3.00	n/a	n/a
HE0502	-10	500	1750	0.50	0.76	3.00	n/a	n/a
HE0685	-10	500	1750	0.50	0.76	3.00	n/a	n/a

HVAC HARDLINE ASSEMBLIES



NOTE: Fitting shown without hose.

Table 3-58: Hose - HVAC - Hardline - Size 6

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
#8 FREON HARDLINE X #8 P80 HOSE X #8 FREON FEMALE 90°								
HE81551	-8	500	2500	0.41	0.74	30.00	n/a	64"
SIZE 6								
HE10601	-6	500	2500	0.31	0.58	2.00	n/a	n/a
HE92691	-6	500	2500	0.31	0.58	2.00	n/a	n/a
SIZE 8								
HE1063	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3147	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3773	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3777	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE3889	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE4559	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE4992	-8	500	2500	0.41	0.68	2.50	n/a	n/a
HE4995	-8	500	2500	0.41	0.68	2.50	n/a	n/a
SIZE 10								
HE1066	-10	500	1750	0.50	0.76	3.00	n/a	n/a
#10 PAD 45°, #12 HOSE, #12 PAD 90°, #10 O-RING, #12 O-RING								
HE5967	n/a	n/a	n/a	n/a	n/a	n/a	n/a	76"
SIZE 12								
HE6317	-12	500	1750	0.63	0.92	4.00	n/a	n/a

HVAC HOSE HARDLINE ASSEMBLY



Table 3-59: Hose - HVAC - A/C Liquid Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length	Cutting Length
A/C LIQUID HARDLINE ASSEMBLY - LIQUID TO CAB								
HE9251	-6	500	2500	0.31	0.58	2.00	n/a	n/a
A/C LIQUID HARDLINE ASSEMBLY - SIZE 6								
HE2935	-6	500	2500	0.31	0.58	2.00	102-13/32"	n/a
HE29361	-6	500	2500	0.31	0.58	2.00	108-5/16"	n/a
HE9243	-6	500	2500	0.31	0.58	2.00	n/a	n/a
HE9245	-6	500	2500	0.31	0.58	2.00	n/a	n/a
HE9815	-6	2250	9000	0.31	0.68	4.00	n/a	n/a
A/C LIQUID HARDLINE ASSEMBLY								
HE9021	-6	500	2500	0.31	0.58	2.00	2200 mm	n/a
HE9281	-6	500	2500	0.31	0.58	2.00	2000 mm	n/a
A/C LIQUID HARDLINE ASSEMBLY - SIZE 6 90° MALE								
HE9271	-6	500	2500	0.31	0.58	2.00	n/a	

HVAC HOSE - A/C SLEEPER HOSE ASSEMBLY - SIZE 6

Table 3-60: Hose - HVAC - A/C Sleeper Hose Assembly - Size 6

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE22541	-6	500	2500	0.31	0.58	2.00	57"

HVAC HOSE - CONDENSER TO FILTER HOSE ASSEMBLY - SIZE 6

Table 3-61: Hose - HVAC - Condenser to Filter Hose Assembly - Size 6

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE0312	-6	500	2500	0.31	0.58	2.00	n/a

HVAC HOSE - COOLANT

Table 3-62: Hose - HVAC - Coolant

TRP® Part No.	Description
HE6112	HVAC Coolant Hose
HE6099	HVAC Coolant Hose

HVAC HOSE - FREON COMPRESSOR HARDLINE ASSEMBLIES



Table 3-63: Hose - HVAC - Freon Compressor Hose Assemblies

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
SIZE 6							
HE3679	-6	500	2500	0.31	0.58	2.00	n/a
SIZE 12							
HE2374	-12	500	1750	0.63	0.92	4.00	n/a
FREON COMPRESSOR SUCTION HOSE ASSEMBLY - SIZE 12							
HE2386	-12	500	1750	0.63	0.92	4.00	n/a

HVAC HOSE - LIQUID TO CAB, HVAC R/D OUTLET X HVAC CAB TXV X A/C HOSE

Table 3-64: Hose - HVAC - Liquid to Cab, HVAC R/D Outlet x HVAC Cab TXV x A/C Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9277	-6	500	2500	0.31	0.58	2.00	n/a

HVAC HOSE - SLEEPER COOLANT

Table 3-65: Hose - HVAC - Sleeper Coolant

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE6255	n/a	n/a	n/a	n/a	n/a	n/a	n/a

HVAC HOSE - SLEEPER COOLANT

Table 3-66: Hose - HVAC - Sleeper Coolant

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9267	-10	n/a	n/a	n/a	n/a	n/a	72"

HVAC HOSE - SUCTION HOSE

Table 3-67: HVAC Hose - Suction Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
---------------	------	-----------------------------	---------------------------	-----------------------	------------------------	--------------------	--------

HVAC SUCTION HOSE - SIZE 10

HE06241	-10	500	1750	0.50	0.76	3.00	162"
HE0625	-10	500	1750	0.50	0.76	3.00	132"
HE0626	-10	500	1750	0.50	0.76	3.00	195"
HE0628	-10	500	1750	0.50	0.76	3.00	180"
HE9403	n/a	n/a	n/a	n/a	n/a	n/a	n/a

HVAC SUCTION HOSE - SIZE 12

HE3431	-12	500	1750	0.63	0.92	4.00	n/a
HE3432	-12	500	1750	0.63	0.92	4.00	n/a
HE3487	-12	500	1750	0.63	0.92	4.00	n/a
HE4001	-12	500	1750	0.63	0.92	4.00	n/a

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE4002	-12	500	1750	0.63	0.92	4.00	n/a
HE40041	-12	500	1750	0.63	0.92	4.00	n/a
HE4022	-12	500	1750	0.63	0.92	4.00	n/a

HVAC SUCTION HOSE - SIZE 12 X SIZE 10

HE0251	-12	500	1750	0.63	0.92	4.00	n/a
HE0252	-12	500	1750	0.63	0.92	4.00	n/a
HE0253	-12	500	1750	0.63	0.92	4.00	n/a
HE0254	-12	500	1750	0.63	0.92	4.00	n/a
HE0255	-12	500	1750	0.63	0.92	4.00	n/a

HVAC HOSE - SUCTION HOSE (AEROQUIP)

Table 3-68: HVAC Hose - Suction Hose (AeroQuip)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE2062	-12	3000	1200	0.75	1.25	3.00	n/a

HVAC HOSE - SUCTION HOSE (B CAB)

Table 3-69: Hose - HVAC - Suction (B Cab)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1479	-12	500	1750	0.63	0.92	4.00	n/a

HVAC HOSE - SUCTION HOSE (B CAB, ISX-EGR)



NOTE: Fitting shown without hose.

Table 3-70: Hose - HVAC - Suction (B Cab, ISX-EGR)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1481	-12	500	1750	0.63	0.92	4.00	2325 mm

HVAC HOSE - UNDER SLEEPER HVAC HARDLINE

Table 3-71: Hose - HVAC - Under Sleeper HVAC Hardline

TRP® Part No.	Description
HE11051	HVAC 4 HOSE Under Sleeper bundle
HE9275	HVAC 4 HOSE Under Sleeper bundle

HYDRAULIC HOSES - #04 FEMALE SAE RUBBER COVERED HOSE ASSEMBLY

Table 3-72: Hose - Hydraulic - #04 Female SAE Rubber Covered Hydraulic Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE2952	-4	3,000	12,000	3/16"	1/2"	3"	25'

HYDRAULIC HOSES - #06 FEMALE SAE 45° FLARE HOSE ASSEMBLY

Table 3-73: Hose - Hydraulic - #06 Female SAE 45° Flare Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE20001	-6	2,250	9,000	5/16"	11/16"	4"	25'

HYDRAULIC HOSES - #06 FEMALE SAE AIR BRAKE BRASS HOSE ASSEMBLY



NOTE: Fitting shown without hose.

Table 3-74: Hose - Hydraulic - #06 Female SAE Air Brake Brass Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1938	-6	2,250	9,000	5/16"	11/16"	4"	375'

HYDRAULIC HOSES - #08 FEMALE JIC HOSE ASSEMBLY

Table 3-75: Hose - Hydraulic - #08 Female JIC Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE8230	-8	2,000	8,000	3/8"	3/4"	4-5/8"	25'

HYDRAULIC HOSES - #08 FEMALE JIC X FEMALE JIC 90° HOSE ASSEMBLY

Table 3-76: Hose - Hydraulic - #08 Female JIC x Female JIC 90° Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE8422	-10	1,750	7,000	1/2"	15/16"	5-1/2"	25'
HE8434	-8	2,000	8,000	3/8"	3/4"	4-5/8"	550'

HYDRAULIC HOSES - #08 FEMALE SAE FLARE AIR HOSE ASSEMBLY



NOTE: Fitting shown without hose.

Table 3-77: Hose - Hydraulic - #08 Female SAE Flare Air Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE16451	-10	1,750	7,000	1/2"	15/16"	5-1/2"	375'

HYDRAULIC HOSES - #16 FEMALE JIC HOSE ASSEMBLY



NOTE: Fitting shown without hose.

Table 3-78: Hose - Hydraulic - #16 Female JIC Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9131	-16	800	3,200	7/8"	1-1/4"	7-3/8"	25'
HE9124	-20	625	2,500	1-1/8"	1-1/2"	9"	10'
HE1554	-24	500	2,000	1-3/8"	1-3/4"	10-1/2"	10'

MISCELLANEOUS HOSES

Table 3-79: Hose - Miscellaneous Hoses

TRP® Part No.	Description	Qty
HE16451	15 mm OD Round Plug, Ribbed Black Polyethylene, PPAP	25

MOLDED HOSES

Table 3-80: Hose - Molded Hoses

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
MOLDED ELBOW HOSE - 70°							
HE3131	n/a	n/a	0.75	3/4	n/a	n/a	n/a

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
---------------	------	-----------------------------	---------------------------	-----------------------	------------------------	--------------------	--------

MOLDED ELBOW HOSE - 90°

HE3127	n/a	0.63	5/8	n/a	n/a	n/a	n/a
--------	-----	------	-----	-----	-----	-----	-----

MOLDED HOSE - 90° - RUBBER

HE7030	2-1/2"	n/a	n/a	n/a	n/a	n/a	n/a
HE8770	n/a	3.00	3.32	n/a	n/a	n/a	n/a

MOLDED HOSE - 90° - SILICONE

HE7014	2" to 2-1/2"	n/a	n/a	n/a	n/a	n/a	n/a
--------	--------------	-----	-----	-----	-----	-----	-----

POGO STICK

Table 3-81: Hose - Pogo Stick

TRP® Part No.	Length	Material	Shape
HE6074	22"	Zinc	3-hole
HE6069	40"	Chrome	D-ring
HE6172	40"	Chrome	D-ring
HE6140	40"	Powder-coated	D-ring
HE6066	40"	Zinc	3-hole
HE6170	40"	Zinc	D-ring

POWER STEERING HOSE ASSEMBLY



NOTE: Fitting shown without hose.

Table 3-82: Hose - Power Steering Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE8420	-8	n/a	n/a	20"	1.09	6.8	43"
HE10951	-8	2,000	8,000	0.41	0.77	4.62	72"
HE1593	-16	800	3,200	0.88	1.23	7.38	n/a
HE1596	-16	800	3,200	0.88	1.23	7.38	n/a
HE1598	-16	800	3,200	0.88	1.23	7.38	n/a
HE1637	-8	2,000	8,000	0.41	0.77	4.62	n/a
HE1189	-8	2,000	8,000	0.41	0.77	4.62	n/a
HE16452	-8	2,000	8,000	0.41	0.77	4.62	n/a
HE10381	-8	500	2,500	0.41	0.68	2.50	n/a
HE1616	-8	500	2,500	0.41	0.68	2.50	n/a
HE2664	-10	n/a	n/a	n/a	n/a	n/a	n/a

POWER STEERING HOSE - "XT" POWER STEERING PUSH-ON HOSE

Table 3-83: Hose - Power Steering Hose - "XT" Power Steering Push-On Hose

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Minimum Bend (in.)	Length	Cover	Standard Packaging Qty.
HE2717	-16	1"						Rubber	50'
HE2715	-10	3/4"						Rubber	100'
HE2713	-10	3/4"						Rubber	50'
HE2707	-8	1/2"						Rubber	50'

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Minimum Bend (in.)	Length	Cover	Standard Packaging Qty.
HE4343	-12	0.75	1.09	n/a	n/a	6.80	43"		
HE41141	-8	0.50	0.82	n/a	n/a	4.00	14"		

PUSH-ON HOSE - FABRIC COVER

Table 3-84: Hose - Push-On Hose - Fabric Cover

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Standard Packaging Qty.
HE2241	-12	250	1,000	3/4"	1"	7"	25'
HE2228	-10	250	1,000	5/8"	7/8"	6"	25'
HE2215	-8	250	1,000	1/2"	3/4"	5"	25'
HE22021	-6	250	1,000	3/8"	5/8"	3"	25'
HE22632	-5	350	1,000	5/16"	9/16"	3"	25'
HE2191	-4	250	1,000	1/4"	1/2"	2-1/2"	25'
HE2277	-8	300	1,200	n/a	n/a	n/a	25'

PUSH-ON HOSE - RUBBER COVER

Table 3-85: Hose - Push-On Hose - Rubber Cover

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Standard Packaging Qty.
HE2293	-10	n/a	n/a	n/a	n/a	n/a	100'
HE2254	-4	n/a	n/a	n/a	n/a	n/a	100'
HE2308	-12	n/a	n/a	n/a	n/a	n/a	25'
HE2291	-10	n/a	n/a	n/a	n/a	n/a	25'
HE22651	-6	n/a	n/a	n/a	n/a	n/a	25'
HE22531	-4	n/a	n/a	n/a	n/a	n/a	25'
HE2305	-12	n/a	n/a	n/a	n/a	n/a	50'
HE22791	-8	n/a	n/a	n/a	n/a	n/a	50'

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Standard Packaging Qty.
HE22661	-6	n/a	n/a	n/a	n/a	n/a	50'
HE4155	-8	125	500	0.5	0.81	4.00	55"
HE4163	-8	125	500	0.5	0.81	4.00	63"
HE5001	-8	250	1,000	0.50	0.75	5.00	850'
HE5007	-12	250	1,000	0.75	1.03	7.00	25'
HE4326	-12	n/a	n/a	0.75	1.09	6.80	n/a
HE4568	-16	n/a	n/a	1.00	1.44	8.50	n/a
HE5002	-8	n/a	n/a	n/a	n/a	n/a	25'

RADIATOR HOSE - 2-1/2" EPDM ISX

Table 3-86: Hose - Radiator Hose - 2-1/2" EPDM ISX

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9348	2-1/2"	n/a	5.35	n/a	n/a	n/a	n/a

RADIATOR HOSE - 2-1/2" SILICONE ISM T



Table 3-87: Hose - Radiator Hose - 2-1/2" Silicone ISM T

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9360	2-1/2"	n/a	n/a	n/a	n/a	n/a	n/a

RADIATOR HOSE - 90°

Table 3-88: Hose - Radiator Hose - 90°

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
RADIATOR HOSE - 90°							
HE7043	2-1/4"	n/a	116	2.5	n/a	n/a	18"
HE7053	2-1/4"	n/a	116	2.5	n/a	n/a	18"
HE7430	1-3/4"	n/a	n/a	n/a	n/a	n/a	n/a
RADIATOR HOSE - 90° 2" EPDM							
HE9339	2"	n/a	n/a	n/a	n/a	n/a	n/a
RADIATOR HOSE - 90° - RUBBER EPDM							
HE9527	2.5	.55 mpa	n/a	2.5	2.91	n/a	n/a
RADIATOR HOSE - 90° - SIZE 36							
HE7492	-36	n/a	n/a	2.25	2.25	n/a	13"

RADIATOR HOSE - EXTREME TEMPERATURE REDUCED REINFORCEMENT SILICONE

Table 3-89: Hose - Extreme Temperature Reduced Reinforcement Silicone Radiator Hose

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)
HE2299	-16	1"	1-5/16"
HE2364	-20	1-1/4"	1-9/16"
HE2416	-22	1-3/8"	1-11/16"
HE2468	-24	1-1/2"	1-13/16"
HE2508	-28	1-3/4"	2-1/16"
HE2546	-32	2"	2-5/16"
HE2585	-36	2-1/4"	2-9/16"
HE2650	-40	2-1/2"	2-13/16"
HE26891	-44	2-3/4"	3-1/16"
HE2728	-48	3"	3-5/16"

RADIATOR HOSE - HEAVY DUTY GENERAL PURPOSE



Table 3-90: Hose - Heavy Duty General Purpose Radiator Hose

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)
HE3270	-16	1"	1-3/8"
HE3452	-40	2-1/2"	2-7/8"
HE3504	-48	3"	3-3/8"

RADIATOR HOSE - HIGH PERFORMANCE MAGNUM ARAMID (SEVERE SERVICE)



Table 3-91: Hose - High Performance Magnum Aramid Radiator Hose (Severe Service)

TRP® Part No.	Size	Inside Diameter (in.)	Outside Diameter (in.)
HE23121	-80	5"	5-3/8"
HE2311	-72	4-1/2"	4-7/8"
HE2310	-64	4"	4-3/8"
HE2309	-56	3-1/2"	3-7/8"
HE2297	-48	3"	3-3/8"
HE2284	-44	2-3/4"	3-1/8"
HE2278	-42	2-5/8"	3"
HE2271	-40	2-1/2"	2-7/8"
HE2263	-38	2-3/8"	2-3/4"
HE2258	-36	2-1/4"	2-5/8"
HE2252	-34	2-1/8"	2-1/2"
HE2245	-32	2"	2-3/8"
HE22371	-30	1-7/8"	2-1/4"
HE2232	-28	1-3/4"	2-1/8"
HE2226	-26	1-5/8"	2"
HE2219	-24	1-1/2"	1-7/8"
HE22101	-22	1-3/8"	1-3/4"
HE2206	-20	1-1/4"	1-5/8"
HE2201	-18	1-1/8"	1-1/2"
HE21931	-16	1"	1-3/8"
HE2192	-14	7/8"	1-1/4"

RADIATOR HOSE - J20R1 D/C 2-PLY 3"



Table 3-92: Hose - Radiator Hose - J20R1 D/C 2-Ply 3"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE5477	-48	n/a	n/a	3.00	3.44	n/a	3'

RADIATOR HOSE - J20R1

Table 3-93: Hose - Radiator Hose - J20R1

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
---------------	------	-----------------------------	---------------------------	-----------------------	------------------------	--------------------	--------

RADIATOR HOSE - SIZE 10 J20R1-A

HE2646	5/8"	n/a	250	0.63	0.96	n/a	n/a
--------	------	-----	-----	------	------	-----	-----

RADIATOR HOSE - SIZE 14 J20R1-A

HE2672	3/4"	n/a	200	0.75	1.08	n/a	n/a
--------	------	-----	-----	------	------	-----	-----

RADIATOR HOSE - SIZE 16 J20R1-A

HE2689	1"	n/a	175	1.00	1.33	n/a	n/a
HE2690	1"	n/a	175	1.00	1.33	n/a	12'

RADIATOR HOSE - SIZE 18 J20R1-A

HE2698	1-1/4'	n/a	275	1.25	1.57	n/a	n/a
--------	--------	-----	-----	------	------	-----	-----

RADIATOR HOSE - SIZE 18 J20R1-D

HE3283	-18	n/a	n/a	1.13	1.53	n/a	n/a
--------	-----	-----	-----	------	------	-----	-----

RADIATOR HOSE - SIZE 20 J20R1-A

HE22041	-20	n/a	n/a	1.25	1.65	n/a	50'
---------	-----	-----	-----	------	------	-----	-----

RADIATOR HOSE - SIZE 20 J20R1-D

HE3296	-20	n/a	n/a	1.25	1.65	n/a	n/a
--------	-----	-----	-----	------	------	-----	-----

RADIATOR HOSE - SIZE 24

HE7122	-24	n/a	n/a	1.50	1.50	15.50	15-1/2"
--------	-----	-----	-----	------	------	-------	---------

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
RADIATOR HOSE - SIZE 24 J20R1-D							
HE3335	-24	n/a	n/a	1.50	1.90	n/a	n/a
RADIATOR HOSE - SIZE 26 J20R1-A							
HE2750	1-5/8"	n/a	250	1.63	1.95	n/a	n/a
RADIATOR HOSE - SIZE 26 J20R1-D							
HE3348	-26	n/a	n/a	1.63	2.03	n/a	n/a
RADIATOR HOSE - SIZE 28 J20R1-D							
HE3361	-28	n/a	n/a	1.75	2.15	n/a	n/a
RADIATOR HOSE - SIZE 32 J20R1-D							
HE3400	-32	n/a	n/a	2.00	2.40	n/a	n/a
RADIATOR HOSE - SIZE 34 J20R1-D							
HE3413	-34	n/a	n/a	2.13	2.53	n/a	n/a
RADIATOR HOSE - SIZE 36 J20R1-D							
HE3426	-36	n/a	n/a	2.25	2.65	n/a	n/a
RADIATOR HOSE - SIZE 38 J20R1-D							
HE3439	-38	n/a	n/a	2.38	2.78	n/a	n/a
RADIATOR HOSE - SIZE 40 J20R1-A							
HE4609	-40	n/a	n/a	2.50	2.94	n/a	4'
RADIATOR HOSE - SIZE 42 J20R1-A							
HE2854	2-5/8"	n/a	150	2.63	2.95	n/a	n/a
RADIATOR HOSE - SIZE 42 J20R1-D							
HE3465	-	n/a	n/a	2.63	3.03	n/a	n/a
RADIATOR HOSE - SIZE 44 J20R1-D							
HE3478	-44	n/a	n/a	2.75	3.15	n/a	n/a
RADIATOR HOSE - SIZE 48							
HE7442	-48	n/a	n/a	3.00	3.00	n/a	16-5/8"
RADIATOR HOSE - SIZE 56 J20R1-A							
HE2893	3-1/2"	n/a	75	3.50	3.82	n/a	n/a
RADIATOR HOSE - SIZE 56 J20R1-D							
HE3530	-56	n/a	n/a	3.50	3.90	n/a	n/a

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
RADIATOR HOSE - SIZE 64 J20R1-A							
HE2906	4"	n/a	50	4.00	4.32	n/a	n/a
RADIATOR HOSE - SIZE 64 J20R1-D							
HE3556	-64	n/a	n/a	4.00	4.40	n/a	n/a

RADIATOR HOSE - J20R4

Table 3-94: Hose - Radiator Hose - J20R4

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE3179	2-1/4"	n/a	n/a	n/a	n/a	n/a	n/a

RADIATOR HOSE - LOWER

Table 3-95: Hose - Lower Radiator Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9536	2-1/2"	.55 mpa	n/a	2.50	2.91	n/a	n/a

RADIATOR HOSE - LOWER RADIATOR COOLANT HOSE

Table 3-96: Hose - Lower Radiator Coolant Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9538	2-1/2"	.55 mpa	n/a	2.50	2.91	n/a	n/a

RADIATOR HOSE - LOWER RADIATOR COOLANT HOSE - C12

Table 3-97: Hose - Lower Radiator Coolant Hose - C12

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9507	2-1/2"	.55 mpa	n/a	2.50	2.91	n/a	n/a

RADIATOR HOSE - OVERFLOW



Table 3-98: Hose - Radiator Overflow

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE8813	n/a	n/a	n/a	n/a	n/a	n/a	n/a

RADIATOR HOSE - UPPER



Table 3-99: Hose - Radiator Hose - Upper

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE9504	2-1/2"	.55 mpa	n/a	2.50	2.91	n/a	n/a
HE9537	2-1/2"	.55 mpa	n/a	2.50	2.91	n/a	n/a

STEEL RADIATOR VENT TUBING

Table 3-100: Hose - Steel Radiator Vent Tubing

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1012	-4	3,000	12,000	0.19	0.52	3.00	n/a
HE1113	-4	3,000	12,000	0.19	0.52	3.00	n/a
HE1134	-4	3,000	12,000	0.19	0.52	3.00	n/a

STEEL RADIATOR VENT TUBING - 3/8"

Table 3-101: Hose - Steel Radiator Vent Tubing - 3/8"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1119	-4	3,000	12,000	0.19	0.52	3.00	n/a

SWIVEL HOSES - FEMALE SWIVEL TO FEMALE SWIVEL HOSE ASSEMBLIES

Table 3-102: Hose - Swivel Hoses - Female Swivel to Female Swivel Hose Assemblies

TRP® Part No.	Size (A)	Size (B)	Thread (A)	Thread (B)	Length
HE1632	-10	-10	7/8" - 14	7/8" - 14	36"
HE1636	-10	-10	7/8" - 14	7/8" - 14	40"
HE1644	-10	-10	7/8" - 14	7/8" - 14	48"
HE16501	-10	-10	7/8" - 14	7/8" - 14	54"
HE1656	-10	-10	7/8" - 14	7/8" - 14	60"
HE1668	-10	-10	7/8" - 14	7/8" - 14	72"
HE1680	-10	-10	7/8" - 14	7/8" - 14	84"

SWIVEL HOSES - FEMALE SWIVEL TO MALE PIPE HOSE ASSEMBLIES

Table 3-103: Hose - Swivel Hoses - Female Swivel to Male Pipe Hose Assemblies

TRP® Part No.	Size (A)	Size (B)	Thread (A)	Thread (B)	Length
HE1932	-10	-8	7/8" - 14	1/2" - 14	36"
HE1944	-10	-8	7/8" - 14	1/2" - 14	48"

TEFLON HOSES

Table 3-104: Teflon Hoses

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE23001	-16	1,000	4,000	7/8"	1"	9"	10'
HE2280	-12	1,200	4,800	5/8"	3/4"	7-3/4"	10'
HE2267	-10	1,500	6,000	1/2"	5/8"	6-1/2"	25'
HE22612	-8	2,500	8,000	3/8"	9/16"	5-1/4"	25'
HE22481	-6	3,000	10,000	5/16"	7/16"	4"	25'
HE22221	-4	3,000	12,000	3/16"	5/16"	2"	25'
HE22191	-3	3,000	12,000	1/8"	1/4"	1-1/2"	25'

TEFLON HOSE - COMPRESSOR DISCHARGE HOSE ASSEMBLY - 45° FEMALE SWIVEL, X 45° MALE FLARE



NOTE: Fitting shown without hose.

Table 3-105: Teflon Hose - Compressor Discharge Hose Assembly - 45° Female Swivel, x 45° Male Flare

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE60741	-10	1,500	6,000	0.50	0.63	n/a	74"

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - #10 FEMALE SAE



NOTE: Fitting shown without hose.

Table 3-106: Teflon Hoses - Compressor Discharge Hose - #10 Female SAE

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE5262	-10	1,500	6,000	0.50	0.63	6.50	28"
HE5241	-10	1,500	6,000	0.50	0.63	6.50	29"
HE5244	-10	1,500	6,000	0.50	0.63	6.50	31"
HE5247	-10	1,500	6,000	0.50	0.63	6.50	34"
HE5250	-10	1,500	6,000	0.50	0.63	6.50	36"
HE5253	-10	1,500	6,000	0.50	0.63	6.50	39"
HE5256	-10	1,500	6,000	0.50	0.63	6.50	42"
HE5259	-10	1,500	6,000	0.50	0.63	6.50	44"
HE5265	-10	1,500	6,000	0.50	0.63	6.50	30"
HE5271	-10	1,500	6,000	0.50	0.63	6.50	35"
HE5274	-10	1,500	6,000	0.50	0.63	6.50	37"
HE5275	-10	1,500	6,000	0.50	0.63	6.50	38"
HE5277	-10	1,500	6,000	0.50	0.63	6.50	40"
HE5280	-10	1,500	6,000	0.50	0.63	6.50	43"
HE5283	-10	1,500	6,000	0.50	0.63	6.50	45"
HE5286	-10	1,500	6,000	0.50	0.63	6.50	47"
HE5289	-10	1,500	6,000	0.50	0.63	6.50	50"
HE5292	-10	500	1,750	0.50	0.76	3.00	52"
HE5295	-10	1,500	6,000	0.50	0.63	6.50	58"
HE5298	-10	1,500	6,000	0.50	0.63	6.50	48"
HE5301	-10	1,500	6,000	0.50	0.63	6.50	53"
HE5304	-10	1,500	6,000	0.50	0.63	6.50	56"
HE53051	-10	1,500	6,000	0.50	0.63	6.50	62"

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - 7/8"- 14 UNF (BOTH ENDS)

Table 3-107: Teflon Hoses - Compressor Discharge Hose - 7/8"- 14 UNF (Both Ends)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1627	-10	1,500	6,000	0.5	0.63	6.50	31"

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - SIZE 10

Table 3-108: Teflon Hoses - Compressor Discharge Hose - Size 10

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE6025	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6026	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6027	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6029	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6031	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6033	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6037	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6039	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6041	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6048	-10	1,500	6,000	0.50	0.63	n/a	n/a
HE6052	-10	1,500	6,000	0.50	0.63	n/a	n/a

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - SIZE 10 FITTING MALE X FEMALE

Table 3-109: Teflon Hoses - Compressor Discharge Hose - Size 10 Fitting Male x Female

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE16401	-10	1,500	6,000	0.50	0.63	6.50	42"
HE1602	-10	1,500	6,000	0.5	0.63	6.50	6"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1612	-10	1,500	6,000	0.5	0.63	6.50	16"
HE1614	-10	1,500	6,000	0.5	0.63	6.50	18"
HE16161	-10	1,500	6,000	0.5	0.63	6.50	20"
HE16201	-10	1,500	6,000	0.5	0.63	6.50	24"
HE1622	-10	1,500	6,000	0.5	0.63	6.50	26"
HE1626	-10	1,500	6,000	0.5	0.63	6.50	30"
HE1628	-10	1,500	6,000	0.5	0.63	6.50	32"
HE1647	-10	1,500	6,000	0.5	0.63	6.50	51"
HE1657	-10	1,500	6,000	0.5	0.63	6.50	61"
HE1686	-10	1,500	6,000	0.5	0.63	6.50	90"
HE1687	-10	1,500	6,000	0.5	0.63	6.50	91"
HE1688	-10	1,500	6,000	0.5	0.63	6.50	92"
HE1696	-10	1,500	6,000	0.5	0.63	6.50	90"
HE1704	-10	1,500	6,000	0.5	0.63	6.50	108"
HE1642	-10	1,500	6,000	0.5	0.63	6.50	46"
HE1716	-10	1,500	6,000	0.5	0.63	6.50	120"

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - SIZE 10 FITTING MALE X MALE



NOTE: Fitting shown without hose.

Table 3-110: Teflon Hoses - Compressor Discharge Hose - Size 10 Fitting Male x Male

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE1920	-10	1,500	6,000	0.50	0.63	6.50	24"
HE1923	-10	1,500	6,000	0.50	0.63	6.50	27"
HE19301	-10	1,500	6,000	0.50	0.63	6.50	34"
HE1992	-10	1,500	6,000	0.50	0.63	6.50	96"

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - SIZE 12



NOTE: Fitting shown without hose.

Table 3-111: Teflon Hoses - Compressor Discharge Hose - Size 12

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE23211	-12	1,500	4,800	0.63	0.76	7.75	25"
HE23221	-12	1,500	4,800	0.63	0.76	7.75	26"
HE23231	-12	1,500	4,800	0.63	0.76	7.75	27"
HE2327	-12	1,500	4,800	0.63	0.76	7.75	31"
HE23281	-12	1,500	4,800	0.63	0.76	7.75	32"
HE2329	-12	1,500	4,800	0.63	0.76	7.75	33"
HE2332	-12	1,500	4,800	0.63	0.76	7.75	36"
HE2333	-12	1,500	4,800	0.63	0.76	7.75	37"
HE2336	-12	1,500	4,800	0.63	0.76	7.75	40"
HE23381	-12	1,500	4,800	0.63	0.76	7.75	42"
HE23392	-12	1,500	4,800	0.63	0.76	7.75	43"
HE2344	-12	1,500	4,800	0.63	0.76	7.75	48"
HE2409	-12	1,200	4,800	0.63	0.75	7.75	48"
HE2347	-12	1,500	4,800	0.63	0.76	7.75	51"

TEFLON HOSES - COMPRESSOR DISCHARGE HOSE - SIZE 12

Table 3-112: Teflon Hoses - Compressor Discharge Hose - Size 12

TRP Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
HE2834	-12	1,200	4,800	0.63	0.76	7.75	34"
HE28361	-12	1,200	4,800	0.63	0.76	7.75	36"

TEFLON HOSES - HIGH TEMPERATURE MP

Table 3-113: Teflon Hose - High Temperature MP

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Length
2807-10HSE	-10	1,500	6,000	0.50	0.63	6.50	10'
HE2316	-20	625	2,500	1.13	1.29	16.00	n/a

TRANSMISSION HOSE HARNESS

Table 3-114: Hose - Transmission Hose Harness

TRP® Part No.	Description
HE4097	Transmission Hose Harness

TRANSMISSION OIL COOLER - STRAIGHT FITTINGS

Table 3-115: Hose - Transmission Oil Cooler - Straight Fittings

TRP® Part No.	Length
HE2666	16"
HE2676	26"
HE2681	31"
HE2686	36"
HE2730	80"
HE2752	102"
HE2754	104"
HE2772	122"
HE2838	188"
HE2852	202"

TRUCK HOSE - LOW TEMPERATURE (ARCTIC HOSE)

Table 3-116: Hose - Low Temperature Truck Hose (Arctic Hose)

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Standard Packaging Qty.
HE2456	-20	625	2,500	1-1/8"	1-1/2"	9"	10'
HE2449	-16	800	3,200	7/8"	1-1/4"	7-3/8"	25'
HE2446	-12	1,500	6,000	5/8"	1-1/16"	6-1/2"	25'
HE2443	-10	1,750	7,000	1/2"	15/16"	5-1/2"	25'
HE2430	-8	2,000	8,000	7/16"	3/4"	4-5/8"	25'
HE2417	-6	2,250	9,000	5/16"	11/16"	4"	25'
HE2411	-5	3,000	12,000	1/4"	9/16"	3-3/8"	25'
HE2404	-4	3,000	12,000	3/16"	1/2"	3"	25'

TRUCK HOSE - MAGNUM FLEX

Table 3-117: Hose - Magnum Flex Truck Hose

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Standard Packaging Qty.
213-10-250HSE	-10	1,250	5,000	1/2"	5/6"	2-1/4"	250'
213-10-50HSE	-10	1,250	5,000	1/2"	5/6"	2-1/4"	50'
213-8-250HSE	-8	1,250	5,000	3/8"	3/4"	1-3/4"	250'
213-8-50HSE	-8	1,250	5,000	3/8"	3/4"	1-3/4"	50'
213-6-250HSE	-6	1,500	6,000	5/16"	5/8"	1-1/4"	250'
213-6-50HSE	-6	1,500	6,000	5/16"	5/8"	1-1/4"	50'
213-5HSE	-5	15,000	6,000	1/4"	9/16"	1"	25'
213-4-50HSE	-4	15,000	6,000	3/16"	1/2"	3/4"	50'
HE2884	1/4"	15,000	6,000	3/16"	1/2"	3/4"	250'
HE2274	-24	500	2,000	1-3/8"	1-3/4"	10-1/2"	10'
HE2261	-20	625	2,500	1-1/8"	1-1/2"	9"	10'
HE2248	-16	800	3,200	7/8"	1-1/4"	7-3/8"	10'
HE2235	-12	1,500	6,000	5/8"	1-1/16"	6-1/2"	10'
HE2223	-10	1,750	7,000	1/2"	15/16"	5-1/2"	100'
HE2222	-10	1,750	7,000	1/2"	15/16"	5-1/2"	250'
HE2225	-10	1,750	7,000	1/2"	15/16"	5-1/2"	50'
HE2210	-8	2,000	8,000	3/8"	3/4"	4-5/8"	100'
HE2209	-8	2,000	8,000	3/8"	3/4"	4-5/8"	250'

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Standard Packaging Qty.
HE2212	-8	2,000	8,000	3/8"	3/4"	4-5/8"	50'
HE2197	-6	2,250	9,000	5/16"	11/16"	4"	100'
HE2196	-6	2,250	9,000	5/16"	11/16"	4"	250'
HE2199	-6	2,250	9,000	5/16"	11/16"	4"	50'
HE2183	-5	3,000	12,000	1/4"	9/16"	3-3/8"	10'
HE21711	-4	3,000	12,000	3/16"	1/2"	3"	100'
HE2173	-4	3,000	12,000	3/16"	1/2"	3"	50'
HE2170	4"	3,000	12,000	3/16"	1/2"	3"	250'

TRAILER HOSE ASSEMBLY



NOTE: Fitting shown without hose.

Table 3-118: Hose - Trailer Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)
HE7091	-6	225	900	3/4"	3/8"	1.75
HE7139	-6	n/a	n/a	3/4"	3/8"	n/a
HE7157	-6	n/a	n/a	3/4"	3/8"	n/a

TURBO HOSE - SILICONE TURBOCHARGER DOUBLE HUMP HOSES

Table 3-119: Turbo Hose - Silicone Turbocharger Double Hump Hoses

TRP® Part No.	Inside Diameter (A) (in.)	Inside Diameter (B) (in.)	Length	Reinforcing Rings	Layers of Nomex
HE4491	3"	3"	5"	No	5
HE4500	4-1/2"	4-1/2"	6"	No	6
HE8137	4"	4-1/2"	6"	No	4
HE8300	3"	3-1/2"	6"	No	4
HE8302	3-1/2"	3-1/2"	6"	No	4
HE8304	4"	4"	5"	No	4
HE8699	4"	4"	6"	Yes	4
HE8689	3"	3"	6"	No	n/a
HE8709	4-1/2"	4-1/2"	6"	No	n/a
HE8728	3"	3"	6"	Yes	n/a
HE8739	3-1/2"	3-1/2"	6"	Yes	n/a
HE8761	4"	4-1/2"	6"	Yes	n/a
HE8774	4-1/2"	4-1/2"	6"	Yes	n/a

WINDSHIELD WASHER & VACUUM TUBING

Table 3-120: Hose - Windshield Washer & Vacuum Tubing

TRP® Part No.	Size (A)	Min. PSI	Inside Diameter (in.)	Outside Diameter (in.)	Standard Packaging Qty.
HE2321	-2	150	1/8"	7/64"	50'
HE2324	-3	100	3/16"	5/32"	50'
HE2328	-3	100	3/16"	5/32"	100'
HE2334	-4	100	1/4"	7/32"	50'
HE23391	-4	100	1/4"	7/32"	150'
HE2341	-5	100	1/4"	9/32"	50'

WIRE BRAID HOSE ASSEMBLIES



NOTE: Fitting shown without hose.

Table 3-121: Hose - Wire Braid Hose Assemblies

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
100R HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 6							
201-6-100HSE	-6	2,250	9,000	0.31	0.68	4.00	100'
100R HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 8							
201-8-250HSE	-8	2,000	8,000	0.41	0.77	4.62	250'
100R HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 10							
201-10-50HSE	-10	1,750	7,000	0.50	0.92	5.50	50'
100R12 3/4" BULK AIR BRAKE HOSE ASSEMBLY - SIZE 12							
HE2096	-12	4,000	16,000	0.75	1.21		50'
100R5 HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 16 - BLACK							
211-16HSE	-16	800	3,200	0.88	1.23	7.38	10'
100R5 HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 4							
201-4-50HSE	-4	3,000	12,000	0.19	0.52	3.00	50'
100R5 HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 6							
201-6-50HSE	-6	2,250	9,000	0.31	0.68	4.00	50'
100R5 HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 8							
201-8-50HSE	-8	2,000	8,000	0.41	0.77	4.62	50'
3/8" BULK AIR BRAKE HOSE ASSEMBLY - SIZE 6							
H38806HSE	-6	225	900	0.38	0.75	1.75	250'
AIR BRAKE HOSE ASSEMBLY - SIZE 10							
HE2029	-10	1,750	7,000	0.50	0.92	5.50	2'
HE2034	-10	1,750	7,000	0.50	0.92	5.50	34"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
AIR BRAKE HOSE ASSEMBLY - #10, CRIMPED FEMALE SWIVEL							
HE2052	-10	1,750	7,000	0.50	0.92	5.50	52"
HE2054	-10	1,750	7,000	0.50	0.92	5.50	54"
AIR BRAKE HOSE ASSEMBLY - SIZE 10							
HE2084	-10	1,750	7,000	0.50	0.92	5.50	84"
HE2130	-10	1,750	7,000	0.50	0.92	5.50	30"
HE2139	-10	1,750	7,000	0.50	0.92	5.50	39"
HE2186	-10	1,750	7,000	0.50	0.92	5.50	86"
HE21941	-10	1,750	7,000	0.50	0.92	5.50	94"
HE6555	-10	675	2,700	0.50	n/a	5.00	22"
HE6565	-10	675	2,700	0.50	n/a	n/a	27"
AIR BRAKE HOSE ASSEMBLY - SIZE 10 - 90° FLARE X STRAIGHT FLARE							
HE7624	-10	1,750	7,000	0.50	0.92	5.50	28"
AIR BRAKE HOSE ASSEMBLY - SIZE 4							
HE10311	-4	3,000	12,000	0.19	0.52	3.00	18"
HE1067	-4	3,000	12,000	0.19	0.52	3.00	36"
HE1081	-4	3,000	12,000	0.19	0.52	3.00	43"
HE11151	-4	3,000	12,000	0.19	0.52	3.00	60"
HE1117	-4	3,000	12,000	0.19	0.52	3.00	61"
HE1127	-4	3,000	12,000	0.19	0.52	3.00	66"
HE1151	-4	3,000	12,000	0.19	0.52	3.00	78"
HE1741	-4	2,000	8,000	0.19	0.52	0.75	416"
HE4817	-4	250	6,000	0.19	0.52	3.00	5"
HE4847	-4	250	6,000	0.19	0.52	3.00	20"
HE4859	-4	250	6,000	0.19	0.52	3.00	26"
HE4863	-4	250	6,000	0.19	0.52	3.00	28"
HE4875	-4	250	6,000	0.19	0.52	3.00	34"
AIR BRAKE HOSE ASSEMBLY - SIZE 6							
HE1309	-6 EPDM	225	900	9.50	19.10	3.50	18"
HE1311	-6 EPDM	225	900	9.50	19.10	3.50	20"
HE1313	-6 EPDM	225	900	9.50	19.10	3.50	22"
HE1314	-6 EPDM	225	900	9.50	19.10	3.50	23"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
HE1315	-6 EPDM	225	900	9.50	19.10	3.50	24"
HE1317	-6 EPDM	225	900	9.50	19.10	3.50	26"
HE1319	-6 EPDM	225	900	9.50	19.10	3.50	28"
HE1321	-6 EPDM	225	900	9.50	19.10	3.50	30"
HE1323	-6 EPDM	225	900	9.50	19.10	3.50	32"
HE1327	-6 EPDM	225	900	9.50	19.10	3.50	36"
HE13301	-6 EPDM	225	900	9.50	19.10	3.50	39"
HE1331	-6 EPDM	225	900	9.50	19.10	3.50	40"
HE1333	-6 EPDM	225	900	9.50	19.10	3.50	42"
HE13351	-6 EPDM	225	900	9.50	19.10	3.50	44"
HE1336	-6 EPDM	225	900	9.50	19.10	3.50	45"
HE1338	-6 EPDM	225	900	9.50	19.10	3.50	48"
HE1343	-6 EPDM	225	900	9.50	19.10	3.50	53"
HE13452	-6 EPDM	225	900	9.50	19.10	3.50	55"
HE1354	-6 EPDM	225	900	9.50	19.10	3.50	64"
HE1361	-6 EPDM	225	900	9.50	19.10	3.50	73"
HE39831	-6	225	900	0.38	0.75	1.75	30"

AIR BRAKE HOSE ASSEMBLY - SIZE 6 CRIMPED

HE1339	-6 EPDM	225	900	9.50	19.10	3.50	49"
--------	---------	-----	-----	------	-------	------	-----

AIR BRAKE HOSE ASSEMBLY - SIZE 8

HE1165	-8	2,000	8,000	0.41	0.77	4.62	70"
HE1508	-8 EPDM	225	900	12.70	22.20	4.00	12"
HE15101	-8 EPDM	225	900	12.70	22.20	4.00	14"
HE1511	-8 EPDM	225	900	12.70	22.20	4.00	15"
HE1512	-8 EPDM	225	900	12.70	22.20	4.00	16"
HE1513	-8 EPDM	225	900	12.70	22.20	4.00	17"
HE1514	-8 EPDM	225	900	12.70	22.20	4.00	18"
HE1516	-8 EPDM	225	900	12.70	22.20	4.00	20"
HE1517	-8 EPDM	225	900	12.70	22.20	4.00	21"
HE1518	-8 EPDM	225	900	12.70	22.20	4.00	22"
HE15201	-8 EPDM	225	900	12.70	22.20	4.00	24"
HE1521	-8 EPDM	225	900	12.70	22.20	4.00	25"
HE1523	-8 EPDM	225	900	12.70	22.20	4.00	27"
HE1524	-8 EPDM	225	900	12.70	22.20	4.00	28"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
HE15251	-8 EPDM	225	900	12.70	22.20	4.00	29"
HE1526	-8 EPDM	225	900	12.70	22.20	4.00	30"
HE1528	-8 EPDM	225	900	12.70	22.20	4.00	32"
HE1532	-8 EPDM	225	900	12.70	22.20	4.00	36"
HE15351	-8 EPDM	225	900	12.70	22.20	4.00	39"
HE1538	-8 EPDM	225	900	12.70	22.20	4.00	42"
HE15391	-8 EPDM	225	900	12.70	22.20	4.00	43"
HE1541	-8 EPDM	225	900	12.70	22.20	4.00	45"
HE1543	-8 EPDM	225	900	12.70	22.20	4.00	47"
HE15451	-8 EPDM	225	900	12.70	22.20	4.00	49"
HE1549	-8 EPDM	225	900	12.70	22.20	4.00	53"
HE15541	-8 EPDM	225	900	12.70	22.20	4.00	58"
HE15551	-8 EPDM	225	900	12.70	22.20	4.00	59"
HE1557	-8 EPDM	225	900	12.70	22.20	4.00	61"
HE1561	-8 EPDM	225	900	12.70	22.20	4.00	65"
HE1562	-8 EPDM	225	900	12.70	22.20	4.00	66"
HE1567	-8 EPDM	225	900	12.70	22.20	4.00	71"
HE1569	-8 EPDM	225	900	12.70	22.20	4.00	73"
HE15751	-8 EPDM	225	900	12.70	22.20	4.00	79"
HE16021	-8 EPDM	225	900	12.70	22.20	4.00	136"
HE1604	-8 EPDM	225	900	12.70	22.20	4.00	146"
HE16051	-8 EPDM	225	900	12.70	22.20	4.00	16"
HE1619	-8 EPDM	225	900	12.70	22.20	4.00	177"
HE1621	-8 EPDM	225	900	12.70	22.20	4.00	184"
HE16221	-8 EPDM	225	900	12.70	22.20	4.00	185"
HE1943	-8 EPDM	225	900	0.50	0.88	2.00	32"
HE1968	-8	225	900	0.50	0.88	2.00	48"
HE3129	-8	2,000	8,000	0.41	0.74	4.62	22"
HE3133	-8	2,000	8,000	0.41	0.74	4.62	24"
HE3141	-8	2,000	8,000	0.41	0.74	4.62	28"
HE59771	-8	750	3,000	10.31	18.85	n/a	17"
HE5983	-8	750	3,000	10.31	18.85	n/a	20"
HE5987	-8	750	3,000	10.31	18.85	n/a	22"
HE5989	-8	750	3,000	10.31	18.85	n/a	23"
HE5999	-8	750	3,000	10.31	18.85	n/a	28"

TRP® Part No.	Size	Max. PSI (Working Pressure)	Min. PSI (Burst Pressure)	Inside Diameter (in.)	Outside Diameter (in.)	Minimum Bend (in.)	Cutting Length
HE6003	-8	750	3,000	10.31	18.85	n/a	30"
HE6015	-8	750	3,000	10.31	18.85	n/a	26"
HE6043	-8	750	3,000	10.31	18.85	3.50	50"
AIR BRAKE HOSE ASSEMBLY - SIZE 8 CRIMPED							
HE1587	-8 EPDM	225	900	12.70	22.20	4.00	103"
AIR BRAKE HOSE ASSEMBLY - SIZE 8 STRAIGHT FITTING X SIZE 8- 90° FITTING							
HE1639	-8	2,000	8,000	0.41	0.77	4.62	47"
AIR & WATER HOSE (NOT COMPATIBLE WITH OIL, FUEL, HYDRAULIC FLUID OR REFRIGERANT)							
HE20801	-10	1,750	7,000	7,000	0.92	5.50	80"
BULK AIR BRAKE HOSE ASSEMBLY - SIZE 4							
HE4505	-4	500	2,000	0.19	0.52	3.00	100'
HYDRAULIC/ AIR HOSE ASSEMBLY - SIZE 6							
HE1945	-6	2,250	9,000	0.31	0.68	4.00	35"

WIRE BRAID HOSE ASSEMBLY - AIR OR WATER HOSE ASSEMBLY



NOTE: Fitting shown without hose.

Table 3-122: Wire Braid Hose Assembly - Air or Water Hose Assembly

TRP® Part No.	Size	Max. PSI (Working Pressure)	Inside Diameter (in.)	Minimum Bend (in.)	Length	Color
HE2058	-10	150	1/2"	2-3/4"	58"	Green
HE20701	-10	150	1/2"	2-3/4"	70"	Green
HE2082	-10	150	1/2"	2-3/4"	82"	Green
HE2094	-10	150	1/2"	2-3/4"	94"	Green
HE21061	-10	150	1/2"	2-3/4"	106"	Green

NOTES

A large grid of graph paper for taking notes, consisting of 20 columns and 30 rows of small squares.

NOTES

A large grid area for taking notes, consisting of many small squares. The grid is approximately 30 columns wide and 50 rows high, providing a structured space for writing or drawing.



*For information, updates, or corrections,
please contact us at support@trparts.com*

*No part of this marketing material may be
reproduced in any manner without written
permission from TRP® North America.*

TRP® North America

750 Houser Way N.
Renton, WA 98057

www.trpparts.com